


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
hasta ↓ 9.370 lm / ↑ 4.370 lm
hasta 138 lm/W
L80 / 50000 h, L90 / 50000 h
Difusor: Microprismatic
DALI-2
IP40

Types



Colours



Distribución luminosa



TASK round


suspended

EN Round luminaire housing in aluminium; ultra low-profile design (only 15 mm); surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; incl. feeder cable or with height adjustable rod suspension (chrome), feed in rod; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; optional: indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; sound absorbing accessories available

ES Luminaria redonda de aluminio; perfil extra plano (sólo 15 mm); superficie con recubrimiento de pintura en polvo; suspendido con cable; regulación de la altura sin necesitar herramientas; incl. cable de alimentación o cable cromado para suspensión ajusable; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; orientación luz por medio de un elemento altamente reflectante; opcional: proporción indirecta con pletinas propias para un flujo luminoso aumentado y una iluminación máxima del techo; iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; disponible accesorio para la absorción del ruido



DiiA® standards
251, 252, 253




DIN EN 12464-1
UGR ≤ 19



direct / indirect
illumination





acoustic
elements



CRI ≥ 98
XPECTRUM
(optional)





TASK 450 ROUND SUSPENDED

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | IP 40 | X-PERT | X-PERT


MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.0 W	3000 K	1750 lm	109 lm/W	059-0ơ4103◪P
	4000 K	1860 lm	116 lm/W	059-0ơ4113◪P

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
37.0 W	3000 K	↧2710/↥1460 lm	113 lm/W	059-0ơ6103◪P
	4000 K	↧2880/↥1550 lm	120 lm/W	059-0ơ6113◪P





TASK 600 ROUND SUSPENDED

CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | IP 40 | X-PERT | X-PERT


MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.6 W	3000 K	3470 lm	117 lm/W	059-0ơ4203◪P
	4000 K	3690 lm	125 lm/W	059-0ơ4213◪P

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
44.0 W	3000 K	↧3470/↥1770 lm	119 lm/W	059-0ơ6203◪P
	4000 K	↧3690/↥1880 lm	127 lm/W	059-0ơ6213◪P





TASK 900 ROUND SUSPENDED

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1-2 ADDR. | IP 40 | X-PERT | X-PERT

MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
51.0 W	3000 K	6630 lm	130 lm/W	059-0ơ4303◪K
	4000 K	7060 lm	138 lm/W	059-0ơ4313◪K

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
100.0 W	3000 K	↧8800/↥4110 lm	129 lm/W	059-0ơ6303◪K
	4000 K	↧9370/↥4370 lm	137 lm/W	059-0ơ6313◪K

Order options

MOUNTING ơ		COLOUR ◪	
cable 1500 mm	2	pure white RAL 9010	7
rod 1000 mm	4	jet black RAL 9005	8
		special colours	X