



Quickinfo

4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
hasta ↓ 19.900 lm / ↑ 10.300 lm
hasta 119 lm/W
L90 / 50000 h
Difusor: Microprismatic
DALI-2
IP20

Types



Colours

Distribución luminosa

TASK circle

suspended

EN Ring-shaped suspended luminaire, consisting of single elements in quarter circle or rectangular shape; Luminaire housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, toolless height adjustment; convenient quick mounting system without tools; incl. feeder cable; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; optional acoustic elements available


ES Luminaria pendular en forma de anillo, compuesta por elementos individuales en forma de cuarto de anillo o bien rectangular; Cuerpo de luminaria de aluminio con cantos redondeados; perfil extra plano (sólo 15 mm); superficie con recubrimiento de pintura en polvo; suspensión cable altura regulable sin herram.; sistema de montaje rápido sin herramientas; incl. cable de alimentación; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; proporción indirecta con pletinas propias para un flujo luminoso aumentado y una iluminación máxima del techo; iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; opcional elementos acústicos disponible




DiiA® standards 251, 252, 253




clicksystem



DIN EN 12464-1
UGR ≤ 19



CRI ≥ 98
XPECTRUM
(optional)





TASK CIRCLE SUSPENDED

CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 4 ADDR. | X-PERT | X-PERT

DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
169.0 W	4000 K	↧13200/↥6870 lm	119 lm/W	0 5 9 - 5 2 8 1 1 3 ◪ K






TASK LONG CIRCLE SUSPENDED


CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 6 ADDR. | X-PERT | X-PERT

DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
253.0 W	4000 K	↧19900/↥10300 lm	119 lm/W	0 5 9 - 5 2 8 2 1 3 ◪ K



Planning Information





TASK long circle
252 W, 4000 K, direct / indirect power

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE ------

Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

Order options


COLOUR ◪	
pure white RAL 9010	7
jet black RAL 9005	8

Compound Semiconductor Applications Catapult, South Wales


Reino Unido

Arquitecto
Monteith Scott

Fotografía
Richard Kiely



Productos utilizados



TASK circle suspended



MINO 100 ceiling / suspended system

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

https://xal.com/es/experimentar-luz/proyectos/pr/compound-semiconductor-applications-catapult-south-wales-282799







https://xal.com/es/experimentar-luz/proyectos/pr/compound-semiconductor-applications-catapult-south-wales-282799



