



MINO 60 CIRCLE

ceiling


EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; sound absorbing elements available; energy-efficient LEDs with very good colour rendering

ES Luminaria con forma de anillo fabricada en aluminio con soldadura de alta calidad; superficie con recubrimiento de pintura en polvo; elemento de luz formado por fundación de aluminio con acabado altamente reflectante para una gestión térmica mejorada; difusor opal de alta calidad que proporciona una iluminación uniforme; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminación y un alumbrado homogéneo; elementos de absorción acústica disponibles; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
 CRI \geq 80 / 3 SDCM (initial MacAdam)
 hasta 145 lm/W
 L90 / 50000 h
 DALI-2
 High Performance Opal,
 Microprismatic
 IP20

Types



Color



Distribución luminosa



DiiA[®] standards
 251, 252, 253



direct / indirect
 illumination



microprismatic



acoustic
 elements




MINO 60 CIRCLE 1000 ceiling



OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
53.0 W	3000 K	6570 lm	124 lm/W	0 3 4 - 2 1 1 2 5 3 <input checked="" type="checkbox"/> H
	4000 K	7480 lm	141 lm/W	0 3 4 - 2 1 1 2 6 3 <input checked="" type="checkbox"/> H



MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
53.0 W	3000 K	5710 lm	108 lm/W	0 3 4 - 2 1 1 2 5 3 <input checked="" type="checkbox"/> Z
	4000 K	6500 lm	123 lm/W	0 3 4 - 2 1 1 2 6 3 <input checked="" type="checkbox"/> Z




MINO 60 CIRCLE 1500 ceiling



OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	10500 lm	127 lm/W	0 3 4 - 2 1 1 0 5 3 <input checked="" type="checkbox"/> H
	4000 K	12000 lm	145 lm/W	0 3 4 - 2 1 1 0 6 3 <input checked="" type="checkbox"/> H



MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	9130 lm	110 lm/W	0 3 4 - 2 1 1 0 5 3 <input checked="" type="checkbox"/> Z
	4000 K	10400 lm	125 lm/W	0 3 4 - 2 1 1 0 6 3 <input checked="" type="checkbox"/> Z




MINO 60 CIRCLE 3000 ceiling



OPAL | DIRECT pure white, CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
167.0 W	3000 K	21200 lm	127 lm/W	0 3 4 - 2 1 1 4 5 3 7 H
	4000 K	24100 lm	144 lm/W	0 3 4 - 2 1 1 4 6 3 7 H



other configurations see MINO 60 CURVE system

Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> G
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8




MINO 60 CIRCLE 6000 ceiling



OPAL | DIRECT pure white, CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
334.0 W	3000 K	42300 lm	127 lm/W	0 3 4 - 2 1 1 6 5 3 7 H
	4000 K	48100 lm	144 lm/W	0 3 4 - 2 1 1 6 6 3 7 H

other configurations see MINO 60 CURVE system




Acoustic accessories (optional)

MINO CIRCLE ACOUSTIC 1000 inlay



COLOUR	Ø-H (mm)	ORDER CODE
marble grey	937-24	0 3 4 - 2 7 0 1 1 1 D
black	937-24	0 3 4 - 2 7 0 1 1 1 L
white	937-24	0 3 4 - 2 7 0 1 1 1 W
limestone	937-24	0 3 4 - 2 7 0 1 1 1 S
anthracite	937-24	0 3 4 - 2 7 0 1 1 1 B
felt grey	937-24	0 3 4 - 2 7 0 1 1 1 G

MINO CIRCLE ACOUSTIC 1500 inlay



COLOUR	Ø-H (mm)	ORDER CODE
marble grey	1434-24	0 3 4 - 2 7 0 2 1 1 D
black	1434-24	0 3 4 - 2 7 0 2 1 1 L
white	1434-24	0 3 4 - 2 7 0 2 1 1 W
limestone	1434-24	0 3 4 - 2 7 0 2 1 1 S
anthracite	1434-24	0 3 4 - 2 7 0 2 1 1 B
felt grey	1434-24	0 3 4 - 2 7 0 2 1 1 G

Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> G
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8

PLANDAY COPENHAGEN

Dinamarca

Lighting Design

Anker & Co

Fotografía

Kris Dekeijser



Productos utilizados



MINO 60 CIRCLE
ceiling



MINO CIRCLE
acoustic inlay

