


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 19
hasta ↓ 4.370 lm / ↑ 9.320 lm
hasta 136 lm/W
L90 / 50000 h
Loxone Air / ESSENTIAL sensor, Loxone Air / touch DIM en el poste, sensor ESSENTIAL independiente, touch DIM en el poste
Microprismatic
IP20

Types



Colours



Distribución luminosa



TASK

free standing

EN Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

ES Luminaria de pie con cabezal de luminaria rectangular de aluminio y cantos redondeados; perfil extra plano (sólo 15 mm); tubo rectangular; pedestal para integrarse como base de mesa; superficie con recubrimiento de pintura en polvo; distribución de luz directa/indirecta que direcciona la luz en el interior de la luminaria mediante LGP (Light Guiding Prism); luz acoplada lateralmente mediante grabado láser orientada hacia arriba y hacia abajo; opcional: proporción indirecta con pletinas propias para un flujo luminoso aumentado; opcional: proporción indirecta con pletinas propias oblicuas para característica de emisión asimétrica; iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; interruptor montado en el tubo; incluye 3 metros de cable de conexión



suitable for double workstation




SENSE sensor on request



lighting control by touch DIM on pole




tunable white 2700 – 6500 K



CRI ≥ 98 XPECTRUM (optional)





TASK free standing u-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29430 ◆ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29431 ◆ Z


MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29420 ◆ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29421 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29410 ◆ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29411 ◆ Z





TASK free standing t-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29530 ◆ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29531 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29520 ◆ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29521 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29510 ◆ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29511 ◆ Z

Order options

CONTROL ◆	
touch DIM on pole	5
stand alone ESSENTIAL sensor	7
Loxone Air / ESSENTIAL sensor	S
Loxone Air / touch DIM on pole	T

COLOUR ◪	
white aluminium RAL 9006	6
pure white RAL 9010	7
jet black RAL 9005	8
special colours	X

OFFICE OMV

Austria

Fotografía
Kurt Kuball



Productos utilizados



TASK free standing

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









