

PABLO basic / focus


EN Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter in spotlight housing; COB (Chip on Board) technology - maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; PABLO basic: high quality aluminium reflector with spherical facet finish; high-gloss anodised; precise radiation characteristic with different light distributions (symmetric / asymmetric); installed and exchanged without tools; PABLO focus: incl. high quality plano-convex glass lens; precise object focusing through adjustable lens; adjustable beam angle of 17-47°; focusing by means of rubberised adjusting ring on the spotlight head; optical attachments as accessories; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, available as an accessory

ES Proyector de carril electrificado de fundición de aluminio inyectado; superficie con recubrimiento de pintura en polvo; giratorio 360° y orientable 310°; convertidor en carcasa de proyector; Chip on Board - máxima eficiencia; no sombras múltiples; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; PABLO basic: reflector de aluminio de alta calidad con diseño facetado esférico; anodizado en brillo intenso; proyección precisa con distribuciones de la luz distintas (simétrica/asimétrica); puede instalarse y cambiarse sin herramientas; PABLO focus: incluye lente de vidrio plano-convexa de alta calidad; enfoque exacto del objeto mediante lente ajustable; ángulo de emisión ajustable de 17° a 47°; enfoque por medio de anillo de ajuste engomado en el cabezal del proyector; los accesorios ópticos como accesorios; adaptador para instalación sin herramientas o desplazamiento en diferentes carriles electrificados de 3 fases; fijación de adaptador sin herramienta con tornillo moleteado o tornillo de sujeción (destornillador necesario); base para techo, opcionalmente en carcasa superpuesta o carcasa empotrada, disponible como accesorio

Quickinfo

3000 K, 4000 K
CRI ≥ 90, CRI ≥ 95 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
hasta 78 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, DIM POTI
IP20

Types



Colours

Distribución luminosa





compatible with MOVE IT PRO 45



DiiA® standards 251, 252, 253




360° rotatable, 310° tiltable




DIM POTI / rotation lock



PABLO BASIC TRACK





SUPER SPOT 6°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	4000 K	681 lm	69 lm/W	1 8 0 - 5 1 ♂ 0 6 ⇕ ◪ V
10.0 W	3000 K	614 lm	61 lm/W	1 8 0 - 5 1 ♂ 0 5 ⇕ ◪ V

3-SDCM

SPOT 12°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	3000 K	986 lm	71 lm/W	1 8 0 - 5 1 ♂ 0 0 ⇕ ◪ S
	4000 K	1080 lm	78 lm/W	1 8 0 - 5 1 ♂ 0 1 ⇕ ◪ S
22.9 W	3000 K	1460 lm	64 lm/W	1 8 0 - 5 1 ♂ 1 0 ⇕ ◪ S
	4000 K	1610 lm	70 lm/W	1 8 0 - 5 1 ♂ 1 1 ⇕ ◪ S

MEDIUM 24°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	3000 K	946 lm	68 lm/W	1 8 0 - 5 1 ♂ 0 0 ⇕ ◪ M
	4000 K	1040 lm	75 lm/W	1 8 0 - 5 1 ♂ 0 1 ⇕ ◪ M
22.9 W	3000 K	1400 lm	61 lm/W	1 8 0 - 5 1 ♂ 1 0 ⇕ ◪ M
	4000 K	1540 lm	67 lm/W	1 8 0 - 5 1 ♂ 1 1 ⇕ ◪ M

FLOOD 39°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	3000 K	914 lm	66 lm/W	1 8 0 - 5 1 ♂ 0 0 ⇕ ◪ F
	4000 K	1000 lm	72 lm/W	1 8 0 - 5 1 ♂ 0 1 ⇕ ◪ F
22.9 W	3000 K	1360 lm	59 lm/W	1 8 0 - 5 1 ♂ 1 0 ⇕ ◪ F
	4000 K	1490 lm	65 lm/W	1 8 0 - 5 1 ♂ 1 1 ⇕ ◪ F

WIDE FLOOD 58°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	3000 K	900 lm	65 lm/W	1 8 0 - 5 1 ♂ 0 0 ⇕ ◪ W
	4000 K	988 lm	71 lm/W	1 8 0 - 5 1 ♂ 0 1 ⇕ ◪ W
22.9 W	3000 K	1340 lm	59 lm/W	1 8 0 - 5 1 ♂ 1 0 ⇕ ◪ W
	4000 K	1470 lm	64 lm/W	1 8 0 - 5 1 ♂ 1 1 ⇕ ◪ W


WALLWASHER CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	3000 K	891 lm	64 lm/W	1 8 0 - 5 1 ♂ 0 0 ⇕ ◪ A
	4000 K	978 lm	70 lm/W	1 8 0 - 5 1 ♂ 0 1 ⇕ ◪ A
22.9 W	3000 K	1320 lm	58 lm/W	1 8 0 - 5 1 ♂ 1 0 ⇕ ◪ A
	4000 K	1450 lm	63 lm/W	1 8 0 - 5 1 ♂ 1 1 ⇕ ◪ A


Order options

MOUNTING	♂	CONTROL	⇕	COLOUR	◪
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8





PABLO FOCUS TRACK



VARIABLE FOCUS 17°-47°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.0 W	3000 K	785 lm	56 lm/W	180 - 52 ♂ 00 ◆ ◪
	4000 K	862 lm	62 lm/W	180 - 52 ♂ 01 ◆ ◪
23.0 W	3000 K	1170 lm	51 lm/W	180 - 52 ♂ 10 ◆ ◪
	4000 K	1280 lm	56 lm/W	180 - 52 ♂ 11 ◆ ◪

Mounting accessories

RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm

Ø·H (mm)	ORDER CODE
151·60	186 - 07227 ◪

SURFACE HOUSING / POINT OUTLET

Ø·H (mm)	ORDER CODE
120·32	186 - 07228 ◪

Optical accessories

HONEYCOMB LOUVER for BO 70 | PABLO

COLOUR	Ø·H (mm)	ORDER CODE
jet black	61·3	080 - 59000018

SNOOT

COLOUR	Ø·H (mm)	ORDER CODE
jet black	62·33	080 - 59000008

Order options

MOUNTING ♂		CONTROL ◆		COLOUR ◪	
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8

Schwedisches Nationalmuseum, Stockholm

Suecia

Arquitecto
Wingårdhs

Lighting Design
Kardorff Ingenieure
Lichtplanung

Fotografía
Linus Lintner



Productos utilizados



PABLO basic / focus

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









