



## SONO IP54

surface


**EN** Round luminaire housing in die-cast aluminium; surface powder coated; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**ES** Cuerpo redondo de aluminio; superficie con recubrimiento de pintura en polvo; apropiada para montaje en techo y paredes; tapa PMMA iluminada homogéneamente con acabado satinado; luminancia idéntica en todos los tamaños; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; luminaria con abertura de 2 orificios para integrar cableado y sencilla conexión

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  80 / 3 SDCM (initial MacAdam)  
 hasta 147 lm/W  
 L90 / 50000 h  
 DALI-2, non atenuable  
 Opal  
 IP54, IK07

### Types



### Color



### Distribución luminosa



DiiA® standards  
 251, 252, 253




easy mounting  
 by click-  
 mechanism



dust & insect  
 protection (IP  
 54)



tunable white  
 2700 – 6500 K  
 (optional)




### SONO 260 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	3000 K	950 lm	136 lm/W	8 7 1 - 9 1 2 6 5 ◆ 7 O
	4000 K	1010 lm	144 lm/W	8 7 1 - 9 1 2 6 6 ◆ 7 O




### SONO 350 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	2090 lm	131 lm/W	8 7 1 - 9 1 3 6 5 ◆ 7 O
	4000 K	2210 lm	139 lm/W	8 7 1 - 9 1 3 6 6 ◆ 7 O




### SONO 450 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	3060 lm	132 lm/W	8 7 1 - 9 1 4 6 5 ◆ 7 O
	4000 K	3240 lm	140 lm/W	8 7 1 - 9 1 4 6 6 ◆ 7 O



#### Order options

CONTROL		◆ COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		




### SONO 600 ip54 surface



#### OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5830 lm	139 lm/W	8 7 1 - 9 1 5 6 5 <span style="color: blue;">◆</span> 7 0
	4000 K	6170 lm	147 lm/W	8 7 1 - 9 1 5 6 6 <span style="color: blue;">◆</span> 7 0



### Mounting tools accessories (optional)

#### DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

#### Order options

CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		