



## SONO LOOP IP54

surface


**EN** Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**ES** Cuerpo redondo de aluminio; superficie con recubrimiento de pintura en polvo; anillo superpuesto de perfil de aluminio enrollado y soldado sin costuras; apropiada para montaje en techo y paredes; tapa PMMA iluminada homogéneamente con acabado satinado; luminancia idéntica en todos los tamaños; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; luminaria con abertura de 2 orificios para integrar cableado y sencilla conexión

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80 / 3 SDCM (initial MacAdam)  
 hasta 136 lm/W  
 L90 / 50000 h  
 DALI-2, non attenuable  
 Opal  
 IP54, IK07

### Types



### Color



### Distribución luminosa




DiiA® standards  
 251, 252, 253




easy mounting  
 by click-  
 mechanism



dust & insect  
 protection (IP  
 54)



tunable white  
 2700 – 6500 K  
 (optional)




### SONO LOOP 260 ip54 surface



#### OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	3000 K	881 lm	126 lm/W	8 7 1 - 8 1 2 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	933 lm	133 lm/W	8 7 1 - 8 1 2 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O




### SONO LOOP 350 ip54 surface



#### OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	8 7 1 - 8 1 3 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	2050 lm	129 lm/W	8 7 1 - 8 1 3 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O




### SONO LOOP 450 ip54 surface




#### OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	8 7 1 - 8 1 4 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	3010 lm	130 lm/W	8 7 1 - 8 1 4 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O



#### Order options

CONTROL		COLOUR	
non DIM	1	grey aluminium RAL 9007	D
DALI-2	3	pure white RAL 9010	7



### SONO LOOP 600 ip54 surface



#### OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5410 lm	129 lm/W	8 7 1 - 8 1 5 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	5730 lm	136 lm/W	8 7 1 - 8 1 5 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O

#### Order options

CONTROL		COLOUR	
non DIM	1	grey aluminium RAL 9007	<input checked="" type="checkbox"/> D
DALI-2	3	pure white RAL 9010	<input type="checkbox"/> 7