


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
hasta 3.260 lm/m
hasta 142 lm/W
L90 / 100000 h
Difusor: Microprismatic, Opal, Reflector
DALI-2
IP20

Types



Colours



Reflector



Distribución luminosa



MINO 40

suspended

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be premounted; remaining luminaire components mounted without tools; pendant fitting with cable suspension; height adjustment without tools; incl. feeder cable; light inset consisting of highly reflective coated extruded profile for improved thermal management; opal cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering


ES Cuerpo de perfil de aluminio con diseño angular; sin tornillos visibles; superficie con recubrimiento de pintura en polvo; perfil de luminaria premontable; resto de componentes luminosos montables sin herramienta; suspendido con cable; altura regulable sin herramientas; incl. cable de alimentación; elemento de luz formado por perfil extruido con acabado altamente reflectante para una gestión térmica mejorada; cubierta opal para iluminación homogénea; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminancia y un alumbrado homogéneo; opcional reflector de alto brillo con óptica facetada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática




DiiA® standards 251, 252, 253



system solution




tunable white 2700 – 6500 K (optional)



CRI ≥ 98 XPECTRUM (optional)





MINO 40 suspended

CRI ≥90 | UGR ≤22 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL | MID LUMEN CRI ≥ 90, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.1 W	1008 mm	3000 K	1470 lm	121 lm/W	0 4 2 - 1 2 1 2 0 3 ◪ H
		4000 K	1470 lm	121 lm/W	0 4 2 - 1 2 1 2 1 3 ◪ H
23.4 W	2008 mm	3000 K	2940 lm	126 lm/W	0 4 2 - 1 2 1 4 0 3 ◪ H
		4000 K	2940 lm	126 lm/W	0 4 2 - 1 2 1 4 1 3 ◪ H
37.0 W	3008 mm	3000 K	4410 lm	119 lm/W	0 4 2 - 1 2 1 6 0 3 ◪ H
		4000 K	4410 lm	119 lm/W	0 4 2 - 1 2 1 6 1 3 ◪ H

OPAL | HIGH LUMEN CRI ≥ 90, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
18.5 W	1008 mm	3000 K	2260 lm	122 lm/W	0 4 2 - 1 2 2 2 0 3 ◪ H
		4000 K	2260 lm	122 lm/W	0 4 2 - 1 2 2 2 1 3 ◪ H
36.0 W	2008 mm	3000 K	4530 lm	126 lm/W	0 4 2 - 1 2 2 4 0 3 ◪ H
		4000 K	4530 lm	126 lm/W	0 4 2 - 1 2 2 4 1 3 ◪ H
61.0 W	3008 mm	3000 K	6790 lm	111 lm/W	0 4 2 - 1 2 2 6 0 3 ◪ H
		4000 K	6790 lm	111 lm/W	0 4 2 - 1 2 2 6 1 3 ◪ H

MICROPRISMATIC | MID LUMEN CRI ≥ 90, DALI-2


SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.1 W	1008 mm	3000 K	1300 lm	107 lm/W	0 4 2 - 1 2 1 2 0 3 ◪ Z
		4000 K	1300 lm	107 lm/W	0 4 2 - 1 2 1 2 1 3 ◪ Z
23.4 W	2008 mm	3000 K	2600 lm	111 lm/W	0 4 2 - 1 2 1 4 0 3 ◪ Z
		4000 K	2600 lm	111 lm/W	0 4 2 - 1 2 1 4 1 3 ◪ Z
37.0 W	3008 mm	3000 K	3890 lm	105 lm/W	0 4 2 - 1 2 1 6 0 3 ◪ Z
		4000 K	3890 lm	105 lm/W	0 4 2 - 1 2 1 6 1 3 ◪ Z

MICROPRISMATIC | HIGH LUMEN CRI ≥ 90, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
18.5 W	1008 mm	3000 K	2000 lm	108 lm/W	0 4 2 - 1 2 2 2 0 3 ◪ Z
		4000 K	2000 lm	108 lm/W	0 4 2 - 1 2 2 2 1 3 ◪ Z
36.0 W	2008 mm	3000 K	4000 lm	111 lm/W	0 4 2 - 1 2 2 4 0 3 ◪ Z
		4000 K	4000 lm	111 lm/W	0 4 2 - 1 2 2 4 1 3 ◪ Z
61.0 W	3008 mm	3000 K	6000 lm	98 lm/W	0 4 2 - 1 2 2 6 0 3 ◪ Z
		4000 K	6000 lm	98 lm/W	0 4 2 - 1 2 2 6 1 3 ◪ Z


Order options

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G
traffic white RAL 9016	W



MINO 40 reflector suspended

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT



REFLECTOR CRI ≥ 90, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	1508 mm	3000 K	chrome	4880 lm	136 lm/W	0 4 2 - 1 2 1 3 0 3 ◪ R
			dark chr.	3630 lm	101 lm/W	0 4 2 - 1 2 1 3 0 3 ◪ B
		4000 K	chrome	4880 lm	136 lm/W	0 4 2 - 1 2 1 3 1 3 ◪ R
			dark chr.	3630 lm	101 lm/W	0 4 2 - 1 2 1 3 1 3 ◪ B
47.0 W	2008 mm	3000 K	chrome	6500 lm	138 lm/W	0 4 2 - 1 2 1 4 0 3 ◪ R
			dark chr.	4840 lm	103 lm/W	0 4 2 - 1 2 1 4 0 3 ◪ B
		4000 K	chrome	6500 lm	138 lm/W	0 4 2 - 1 2 1 4 1 3 ◪ R
			dark chr.	4840 lm	103 lm/W	0 4 2 - 1 2 1 4 1 3 ◪ B
67.0 W	3008 mm	3000 K	chrome	9510 lm	142 lm/W	0 4 2 - 1 2 1 6 0 3 ◪ R
			dark chr.	7090 lm	106 lm/W	0 4 2 - 1 2 1 6 0 3 ◪ B
		4000 K	chrome	9510 lm	142 lm/W	0 4 2 - 1 2 1 6 1 3 ◪ R
			dark chr.	7090 lm	106 lm/W	0 4 2 - 1 2 1 6 1 3 ◪ B

Order options

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G
traffic white RAL 9016	W