




Quickinfo

6500 K
hasta 217 lm/W
DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20, IP40, back IP20

Types



Colours

Set de montaje

SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement

ES Inserto redondo (luz emergencia/sensor); instalación sin herramientas mediante kit de montaje (con o sin marco); superficie lacada; posibilidad de instalar distintas carcasas; inserto luz de emerg. LED: 3 variantes con difer. opciones de test - Basic con botón de prueba, autotest con LED de estado o Pro DALI con superv. a través de DALI; sensor con control DALI-2: 2 variantes - Basic con sensor de luminosidad y presencia o Pro con medición adic. de temperatura, humedad y calidad del aire y nivel de ruido



quick mounting
in
soft acoustic
ceilings



60



SASSO 60 round sensor essential


360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | presence | brightness

DALI-2 ESSENTIAL sensor

COLOUR	ORDER CODE
jet black	048 - 269311 1
traffic white	048 - 269311 7



65



SASSO 60 round sensor sense


360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | brightness | presence | temp. | sound pr. | CO_2 | humidity

DALI-2 SENSE sensor

COLOUR	ORDER CODE
jet black	048 - 269312 1
traffic white	048 - 269312 7



110



SASSO 60 round emergency light

360° | CRI ≥ 80 | 220-240 V

3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048 - 269321 ◪

incl. 3 interchangeable lenses

3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048 - 269322 ◪

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048 - 269323 ◪

incl. 3 interchangeable lenses

Order options

COLOUR	◪	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/20/25 mm	73·29	048-2696117

for SASSO 60 round | SPIO 60 downlight




MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	80·25	048-2696197



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·27	048-2696397
jet black	80·27	048-2696398



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm


COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·40	048-2696317
jet black	80·40	048-2696318

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	048-2695210



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-2695110

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings

COLOUR	L·W·H (mm)	ORDER CODE
traffic black	77·77·35	048-2695918

Order options

COLOUR	
white aluminium	RAL 9006
traffic black	RAL 9017

Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE	ORDER CODE
3h battery life	048-269390