






Types



Distribución luminosa



SASSO PRO 80 adjustable flush square

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system; surface powder coated; with trim (square); installation possible in different housings; light inset rotatable and tiltable; optical attachments available as accessories; with optional high-quality lens system with precise radiation characteristic; and high-quality reflector with spherical facet effect design, precise radiation characteristic with two different beam angles; installed and exchanged without tools; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo de inyección en aluminio; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie con recubrimiento de pintura en polvo; con marco (cuadrado); posibilidad de instalar distintas carcasas; elemento de luz girable e inclinable; los accesorios ópticos están disponibles como accesorios; opcionalmente con sistema óptico de lentes de alta calidad con precisa característica de emisión; o bien reflector de alta calidad con óptica facetada esférica, precisa característica de emisión con dos diferentes ángulos de emisión; intercambiable sin herramienta; con tecnología COB (Chip on Board) o LEDS de alta potencia para proporcionar una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



360° rotatable, 35° tiltable



Colour Warm Dimming 1800 – 2700 K



SASSO PRO 80 adjustable

35° 360° | CRI ≥95 | 2 SDCM | UGR ≤10 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT





SUPER SPOT 8°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	2700 K	388 lm	55 lm/W	048-231041 ◪ V
	3000 K	379 lm	54 lm/W	048-231051 ◪ V
	4000 K	408 lm	58 lm/W	048-231061 ◪ V


MEDIUM 26°,

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.5 W	CWD, CRI ≥ 95	377 lm	58 lm/W	048-231 0E3 ◪ M
7.5 W	2700 K, CRI ≥ 90	721 lm	96 lm/W	048-231041 ◪ M
	3000 K, CRI ≥ 90	757 lm	101 lm/W	048-231051 ◪ M
	4000 K, CRI ≥ 90	765 lm	102 lm/W	048-231061 ◪ M
12.2 W	2700 K, CRI ≥ 90	1010 lm	83 lm/W	048-231 24 ◪ M
	3000 K, CRI ≥ 90	1050 lm	86 lm/W	048-231 25 ◪ M
	4000 K, CRI ≥ 90	1120 lm	92 lm/W	048-231 26 ◪ M

FLOOD 37°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.5 W	2700 K	728 lm	97 lm/W	048-231041 ◪ F
	3000 K	765 lm	102 lm/W	048-231051 ◪ F
	4000 K	773 lm	103 lm/W	048-231061 ◪ F
12.2 W	2700 K	1020 lm	84 lm/W	048-231 24 ◪ F
	3000 K	1060 lm	87 lm/W	048-231 25 ◪ F
	4000 K	1130 lm	93 lm/W	048-231 26 ◪ F

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 10
DALI cable ø 4 – 12 mm	105·58·30	005-255111 10

Linect®-Ready

Mounting accessories (required)




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

L·W·H (mm)	ORDER CODE
98·98·43	052-194231 ◪

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
229·227·160	060-00080

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
240·400·130	052-19143 20

order mounting set separately

Optical accessories (optional)



HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
54·11	048-20913 1

LINEAR PRISMATIC LENS

Ø·H (mm)	ORDER CODE
54·11	048-20923 1



SNOOT

Ø·H (mm)	ORDER CODE
54·25	048-20911 1



SNOOT WITH HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
54·25	048-20912 1

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8