


Quickinfo

2700 K, 3000 K, 4000 K, colour warm dimming 2000 - 3000 K, tunable white 1800 - 3000 K, tunable white 2700 - 6500 K
CRI ≥ 90, CRI ≥ 92, CRI ≥ 95 / 3 SDCM (initial MacAdam), 4 SDCM (initial MacAdam)
UGR ≤ 19
hasta 105 lm/W
L70 / 50000 h, L80 / 50000 h, L85 / 50000 h
DALI-2, non atenuable
front IP20

Types



Colours

Set de montaje

Distribución luminosa

SASSO PRO 100 adjustable flush square

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system; surface powder coated; with trim (square); light inset rotatable and tiltable; optical attachments available as accessories; high-quality reflector with spherical facet effect design, precise radiation characteristics with different beam angles; installed and exchanged without tools; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo de inyección en aluminio; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie con recubrimiento de pintura en polvo; con marco (cuadrado); elemento de luz girable e inclinable; los accesorios ópticos están disponibles como accesorios; bien reflector de alta calidad con óptica facetada esférica, precisa característica de emisión con diferentes ángulos de emisión; intercambiable sin herramienta; Chip on Board que proporciona una máxima eficiencia; no proporciona sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



360° rotatable, 35° tiltable




Colour Warm Dimming 2000 – 3000 K



tunable white 1800 – 3000 K or 2700 – 6500 K







SASSO PRO 100 adjustable

35° 360° | CRI ≥ 95 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT

SPOT 17°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	048-241045 S
	3000 K	1410 lm	96 lm/W	048-241055 S
	4000 K	1490 lm	101 lm/W	048-241065 S
27.0 W	2700 K	2170 lm	80 lm/W	048-241245 S
	3000 K	2270 lm	84 lm/W	048-241255 S
	4000 K	2400 lm	89 lm/W	048-241265 S

MEDIUM 24°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	048-241045 M
	3000 K	1410 lm	96 lm/W	048-241055 M
	4000 K	1490 lm	101 lm/W	048-241065 M
27.0 W	2700 K	2170 lm	80 lm/W	048-241245 M
	3000 K	2270 lm	84 lm/W	048-241255 M
	4000 K	2400 lm	89 lm/W	048-241265 M

FLOOD 36°-38°,

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K, CRI ≥ 90	1360 lm	93 lm/W	048-241045 F
	3000 K, CRI ≥ 90	1420 lm	97 lm/W	048-241055 F
	4000 K, CRI ≥ 90	1500 lm	102 lm/W	048-241065 F
14.9 W	CWD, CRI ≥ 95	853 lm	57 lm/W	048-241113 F
27.0 W	2700 K, CRI ≥ 90	2190 lm	81 lm/W	048-241245 F
	3000 K, CRI ≥ 90	2280 lm	84 lm/W	048-241255 F
	4000 K, CRI ≥ 90	2420 lm	90 lm/W	048-241265 F

WIDE FLOOD 57°, CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1280 lm	87 lm/W	048-241045 W
	3000 K	1340 lm	91 lm/W	048-241055 W
	4000 K	1420 lm	97 lm/W	048-241065 W
27.0 W	2700 K	2070 lm	77 lm/W	048-241245 W
	3000 K	2160 lm	80 lm/W	048-241255 W
	4000 K	2280 lm	84 lm/W	048-241265 W

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8







SASSO PRO 100 adjustable high output

35° 360° | CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

MEDIUM 26°, CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2790 lm	103 lm/W	0 4 8 - 2 4 1 3 5 ◆ ◪ M
	4000 K	2820 lm	104 lm/W	0 4 8 - 2 4 1 3 6 ◆ ◪ M

FLOOD 39°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2810 lm	104 lm/W	0 4 8 - 2 4 1 3 5 ◆ ◪ F
	4000 K	2840 lm	105 lm/W	0 4 8 - 2 4 1 3 6 ◆ ◪ F








SASSO PRO 100 adjustable (tunable white)

35° 360° | TUNABLE WHITE | CRI ≥ 92 | 220-240 V | 2 ADDR. | X-PERT | X-PERT

FLOOD 38°, CRI ≥ 92, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
21.0 W	tunable w., 1800 - 3000 K	1450 lm	69 lm/W	0 4 8 - 2 4 1 2 L 3 ◪ F
28.2 W	tunable w., 2700 - 6500 K	2180 lm	77 lm/W	0 4 8 - 2 4 1 2 D 3 ◪ F

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

L·W·H (mm)	ORDER CODE
112·112·43	0 5 2 - 1 9 4 2 4 1 ◪

Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
240·400·130	052-191442 0

order mounting set separately

Optical accessories (optional)

HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·11	048-219131

LINEAR PRISMATIC LENS

Ø·H (mm)	ORDER CODE
74·11	048-219231



SNOOT

Ø·H (mm)	ORDER CODE
74·25	048-219111



SNOOT WITH HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·25	048-219121

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8