




MIRA 150

recessed

EN Round recessed spotlight in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25mm; surface powder coated; installation without tools using snap spring closure; lighting level recessed; completely homogeneously illuminated, satinised or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion


ES Proyector empotrable redondo de inyección en aluminio; con marco; para instalación en techos de 2-25mm de grosor; superficie con recubrimiento de pintura en polvo; sencilla instalación sin herramientas mediante un enganche elástico; lámpara retrasada; iluminación homogénea, con efecto opal o microprismático; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; convertidor externo para inserción en el techo

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM (initial MacAdam)
hasta 128 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non attenuable
Microprismatic, Opal
front IP20, IP54, back IP20

Types

MIRA round



Colours



Distribución luminosa






MIRA 150 round trim



OPAL CRI ≥ 90


SYSTEM	COLOUR TEMP.	COLOUR	LUM. FLUX	EFFICACY	ORDER CODE
13.0 W	3000 K	jet black	1380 lm	106 lm/W	5 2 - 9 3 2 3 5 8 O
		pure white	1500 lm	115 lm/W	5 2 - 9 3 2 3 5 7 O
	4000 K	jet black	1520 lm	117 lm/W	5 2 - 9 3 2 3 6 8 O
		pure white	1660 lm	128 lm/W	5 2 - 9 3 2 3 6 7 O
18.6 W	3000 K	jet black	1850 lm	99 lm/W	5 2 - 9 3 2 4 5 8 O
		pure white	2020 lm	109 lm/W	5 2 - 9 3 2 4 5 7 O
	4000 K	jet black	2040 lm	110 lm/W	5 2 - 9 3 2 4 6 8 O
		pure white	2220 lm	119 lm/W	5 2 - 9 3 2 4 6 7 O



MICROPRISMATIC CRI ≥ 90

SYSTEM	COLOUR TEMP.	COLOUR	LUM. FLUX	EFFICACY	ORDER CODE
13.0 W	3000 K	jet black	1340 lm	103 lm/W	5 2 - 9 3 2 3 5 8 P
		pure white	1470 lm	113 lm/W	5 2 - 9 3 2 3 5 7 P
	4000 K	jet black	1480 lm	114 lm/W	5 2 - 9 3 2 3 6 8 P
		pure white	1620 lm	125 lm/W	5 2 - 9 3 2 3 6 7 P
18.6 W	3000 K	jet black	1800 lm	97 lm/W	5 2 - 9 3 2 4 5 8 P
		pure white	1970 lm	106 lm/W	5 2 - 9 3 2 4 5 7 P
	4000 K	jet black	1980 lm	106 lm/W	5 2 - 9 3 2 4 6 8 P
		pure white	2170 lm	117 lm/W	5 2 - 9 3 2 4 6 7 P

Electrical mounting accessories



THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Order options

IP RATING FRONT	CONTROL	COLOUR	
IP20	0 non DIM	1 pure white	RAL 9010
IP54	8 DALI-2	3 jet black	RAL 9005