Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
hasta 3.090 lm/m
hasta 143 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non atenuable
Microprismatic, Opal
IP20

Types



Colours

Distribución luminosa





DiiA® standards
251, 252, 253



system solution



DIN EN 12464-1
UGR ≤ 19



tunable white
2700 – 6500 K
(optional)



CRI ≥ 98
XPECTRUM
(optional)

MINIMAL 100

trimless

EN Luminaire housing made of extruded aluminium; for trimless installation in plasterboard ceilings; special edge design with grooves for better adhesion of filler; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile for mounting available in advance; remaining luminaire components mounted without tools; light inset consisting of highly reflective coated extruded profile for improved thermal management; opal cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; energy-efficient LEDs with very good colour rendering

ES Cuerpo de lámpara de perfil extrusionado de aluminio; apropiada para montaje sin marco en techos de yeso; con diseño especial en los bordes para facilitar una mejor fijación del producto ; apropiada para grosores de techo entre 8-25 mm; superficie con recubrimiento de pintura en polvo; perfil disponible para pre-montaje; resto de componentes luminosos montables sin herramienta; elemento de luz formado por perfil extruido con acabado altamente reflectante para una gestión térmica mejorada; cubierta opal para iluminación homogénea; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminancia y un alumbrado homogéneo; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

MINIMAL 100 trimless



MICROPRISMATIC | MID LUMEN traffic white, CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.0 W	576 mm	3000 K	932 lm	117 lm/W	052-33L25170
		4000 K	987 lm	123 lm/W	052-33L26170
11.9 W	876 mm	3000 K	1400 lm	118 lm/W	052-33L35170
		4000 K	1480 lm	124 lm/W	052-33L36170
15.3 W	1176 mm	3000 K	1860 lm	122 lm/W	052-33L45170
		4000 K	1970 lm	129 lm/W	052-33L46170
19.2 W	1476 mm	3000 K	2330 lm	121 lm/W	052-33L55170
		4000 K	2470 lm	129 lm/W	052-33L56170
30.0 W	2348 mm	3000 K	3730 lm	124 lm/W	052-33L85170
		4000 K	3950 lm	132 lm/W	052-33L86170

OPAL | MID LUMEN traffic white, CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.0 W	576 mm	3000 K	1010 lm	126 lm/W	052-33L25170H
		4000 K	1070 lm	134 lm/W	052-33L26170H
11.9 W	876 mm	3000 K	1520 lm	128 lm/W	052-33L35170H
		4000 K	1600 lm	134 lm/W	052-33L36170H
15.3 W	1176 mm	3000 K	2020 lm	132 lm/W	052-33L45170H
		4000 K	2140 lm	140 lm/W	052-33L46170H
19.2 W	1476 mm	3000 K	2530 lm	132 lm/W	052-33L55170H
		4000 K	2670 lm	139 lm/W	052-33L56170H
30.0 W	2348 mm	3000 K	4040 lm	135 lm/W	052-33L85170H
		4000 K	4280 lm	143 lm/W	052-33L86170H

MICROPRISMATIC | HIGH LUMEN traffic white, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	576 mm	3000 K	1540 lm	112 lm/W	052-33M25⇕7
		4000 K	1630 lm	118 lm/W	052-33M26⇕7
20.6 W	876 mm	3000 K	2310 lm	112 lm/W	052-33M35⇕7
		4000 K	2450 lm	119 lm/W	052-33M36⇕7
27.5 W	1176 mm	3000 K	3080 lm	112 lm/W	052-33M45⇕7
		4000 K	3260 lm	119 lm/W	052-33M46⇕7
34.0 W	1476 mm	3000 K	3850 lm	113 lm/W	052-33M55⇕7
		4000 K	4080 lm	120 lm/W	052-33M56⇕7
53.0 W	2348 mm	3000 K	6160 lm	116 lm/W	052-33M85⇕7
		4000 K	6520 lm	123 lm/W	052-33M86⇕7

Order options

CONTROL ⇕		COVER OPTION ◘		COLOUR	
non DIM	1	microprismatic (glare reduced)	G	traffic white	RAL 9016
DALI-2	3	microprismatic	Z		

OPAL | HIGH LUMEN traffic white, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	576 mm	3000 K	1670 lm	121 lm/W	052-33M25 ⬍ 7H
		4000 K	1770 lm	128 lm/W	052-33M26 ⬍ 7H
20.6 W	876 mm	3000 K	2510 lm	122 lm/W	052-33M35 ⬍ 7H
		4000 K	2650 lm	129 lm/W	052-33M36 ⬍ 7H
27.5 W	1176 mm	3000 K	3340 lm	121 lm/W	052-33M45 ⬍ 7H
		4000 K	3540 lm	129 lm/W	052-33M46 ⬍ 7H
34.0 W	1476 mm	3000 K	4180 lm	123 lm/W	052-33M55 ⬍ 7H
		4000 K	4420 lm	130 lm/W	052-33M56 ⬍ 7H
53.0 W	2348 mm	3000 K	6680 lm	126 lm/W	052-33M85 ⬍ 7H
		4000 K	7070 lm	133 lm/W	052-33M86 ⬍ 7H

Mounting accessories

CONCRETE INSTALLATION HOUSING

L·W·H (mm)	ORDER CODE
635·116·94	036-05066
935·116·94	036-05096
1235·116·94	036-05126
1535·116·94	036-05156
2407·116·94	036-05236

no use for wall installation (only on request)

Order options

CONTROL ⬍	
non DIM	1
DALI-2	3

COLOUR	
traffic white	RAL 9016