


Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
hasta 104 lm/W
L80 / 50000 h
non atenuable
IP54, IK07, IK09

Types



Colours


Distribución luminosa

DOC

surface

EN Round surface mounted luminaire, housing in die-cast aluminium; central decorative disc made of galvanized sheet steel attached by magnet; surface powder coated; opal cover for completely homogeneous illumination; with increased transmission and diffusion; energy-efficient LEDs with very good colour rendering; degree of protection IP54, with pressure compensation valve; ambient temperatures from -20°C to + 50°C; ø180 mm: suitable for through wiring

ES Luminaria de superficie con forma redonda, cuerpo de aluminio; disco decorativo central de chapa de acero cincada fijado por medio de imán; superficie con recubrimiento de pintura en polvo; cubierta opal para iluminación homogénea; con alta refracción y difusión de la luz; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; tipo protección IP 54, con válvula compensación presión; temperatura ambiente de -20°C a +50°C; ø 180 mm: apropiado para cableado pasante



DOC 180 surface

CRI ≥ 80 | 220-240 V | IP54 | IK07 | X-PERT | X-PERT

OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.5 W	3000 K	1340 lm	99 lm/W	0 8 8 - 2 7 1 0 5 1






DOC 360 surface

CRI ≥ 80 | 220-240 V | IP54 | IK 09 | X-PERT | X-PERT

OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.8 W	3000 K	2890 lm	104 lm/W	0 8 8 - 2 7 2 0 5 1



Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8
grey aluminium RAL 9007	D