






Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
hasta 187 lm/W
L90 / 100000 h
DALI-2, non atenuable
Reflector
IP20

Types



Distribución luminosa



MITA circle 160

recessed

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim (suitable for ceiling thickness of 2-25 mm); or for trimless installation in plasterboard ceilings (suitable for ceiling thickness of 12.5/15/20/25 mm); surface powder coated; incl. blind cover made of plastic in the cut-out; optional: SASSO 60 round, SASSO 60 round sensor, SASSO 60 round emergency or SPIO 60 for installation in the cut-out available as an accessory; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

ES Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; luminaria empotrable con marco (para instalación en techos de 2-25 mm de grosor); o para montaje sin marco en techos de escayola (para instalación en techos con grosor de 12,5/15/20/25 mm); superficie con recubrimiento de pintura en polvo; con cubierta opaca de plástico en el recorte de techo; opcional: SASSO 60 round, SASSO 60 round sensor, SASSO 60 round emergency o SPIO 60 para la inserción en el recorte de techo disponible como accesorio; reflector de alto brillo con óptica facetada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



DIN EN 12464-1
UGR ≤ 19




trimless installation in plasterboard



SASSO 60 inset ready




tunable white
2700 – 6500 K




MITA CIRCLE 160 TRIM

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | III | DALI 1 ADDR. | X-PERT




REFLECTOR

FIXTURE	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
5.7 W, 22 Vf, 375 mA	tunable w.	90	chrome	859 lm	151 lm/W	074-81222D1 ◪ R
			dark chr.	615 lm	108 lm/W	074-81222D1 ◪ B
6.4 W, 22 Vf, 300 mA	3000 K	80	chrome	1120 lm	175 lm/W	074-81225 1 ◪ R
			dark chr.	799 lm	125 lm/W	074-81225 1 ◪ B
		90	chrome	973 lm	153 lm/W	074-81220 1 ◪ R
			dark chr.	696 lm	109 lm/W	074-81220 1 ◪ B
	4000 K	80	chrome	1190 lm	187 lm/W	074-81226 1 ◪ R
			dark chr.	853 lm	134 lm/W	074-81226 1 ◪ B
		90	chrome	973 lm	153 lm/W	074-81221 1 ◪ R
			dark chr.	696 lm	109 lm/W	074-81221 1 ◪ B



MITA CIRCLE 160 TRIMLESS

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | III | DALI 1 ADDR. | X-PERT



REFLECTOR

FIXTURE	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
5.7 W, 22 Vf, 375 mA	tunable w.	90	chrome	859 lm	151 lm/W	074-82222D1 ◪ R
			dark chr.	615 lm	108 lm/W	074-82222D1 ◪ B
6.4 W, 22 Vf, 300 mA	3000 K	80	chrome	1120 lm	175 lm/W	074-82225 1 ◪ R
			dark chr.	799 lm	125 lm/W	074-82225 1 ◪ B
		90	chrome	973 lm	153 lm/W	074-82220 1 ◪ R
			dark chr.	696 lm	109 lm/W	074-82220 1 ◪ B
	4000 K	80	chrome	1190 lm	187 lm/W	074-82226 1 ◪ R
			dark chr.	853 lm	134 lm/W	074-82226 1 ◪ B
		90	chrome	973 lm	153 lm/W	074-82221 1 ◪ R
			dark chr.	696 lm	109 lm/W	074-82221 1 ◪ B

Order options

COLOUR	◪
traffic white RAL 9016	7
jet black RAL 9005	8

Planning Information




Electrical accessories (required)

POWER SUPPLY

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA | 44 W | DALI-2 | PC2	176-264 V AC	η 89 %	97·43·30	0 0 2 - 9 1 1 2 0
375 mA | 45 W | DALI-2 | PC1	198-264 V AC	η 88 %	129·79·30	0 0 2 - 9 1 1 2 1
300 mA | 22 W | non DIM | PC2	198-264 V AC	η 89 %	147·44·22	0 0 2 - 9 1 1 2 2

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER


TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	0 0 5 - 6 1 2 1 0 3 0

200 -1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10 – 40 V SELV

Allplan, Graz

Austria


Fotografía
Tim Ertl




Productos utilizados




BETO free standing



BETO circle suspended



MITA circle 160 recessed



MITA circle 240 / 450 recessed



MITA circle 450 suspended

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com














#VERANTWORTUNG
#MENSCH
#ZUKUNFT

