






Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
hasta 163 lm/W
L90 / 100000 h, L90 / 75000 h
DALI-2
Reflector
IP20

Types



Colours



Reflector



Distribución luminosa



MITA circle 240 / 450

recessed

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

ES Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; luminaria empotrable con marco; opcional: cubierta opaca para inserción en recorte de techo disponible como accesorio adicional; para instalación en techos de 2-25 mm de grosor; superficie con recubrimiento de pintura en polvo; reflector de alto brillo con óptica facetada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática




suitable for plasterboard or grid ceilings



DIN EN 12464-1
UGR ≤ 19




tunable white
2700 – 6500 K




MITA CIRCLE 240 trim

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT




REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W	tunable w.	90	chrome	1720 lm	128 lm/W	074-81144D3 R
			dark chr.	1230 lm	92 lm/W	074-81144D3 B
13.8 W	3000 K	80	chrome	2080 lm	151 lm/W	074-81145 3 R
			dark chr.	1490 lm	108 lm/W	074-81145 3 B
		90	chrome	1810 lm	131 lm/W	074-81140 3 R
			dark chr.	1300 lm	94 lm/W	074-81140 3 B
	4000 K	80	chrome	2220 lm	161 lm/W	074-81146 3 R
			dark chr.	1590 lm	115 lm/W	074-81146 3 B
		90	chrome	1810 lm	131 lm/W	074-81141 3 R
			dark chr.	1300 lm	94 lm/W	074-81141 3 B



MITA CIRCLE 450 trim

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT



REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
26.8 W	tunable w.	90	chrome	3440 lm	128 lm/W	074-81166D3 R
			dark chr.	2460 lm	92 lm/W	074-81166D3 B
29.4 W	3000 K	80	chrome	4500 lm	153 lm/W	074-81165 3 R
			dark chr.	3220 lm	110 lm/W	074-81165 3 B
		90	chrome	3920 lm	133 lm/W	074-81160 3 R
			dark chr.	2800 lm	95 lm/W	074-81160 3 B
	4000 K	80	chrome	4790 lm	163 lm/W	074-81166 3 R
			dark chr.	3430 lm	117 lm/W	074-81166 3 B
		90	chrome	3920 lm	133 lm/W	074-81161 3 R
			dark chr.	2800 lm	95 lm/W	074-81161 3 B
40.0 W	3000 K	80	chrome	5850 lm	146 lm/W	074-81265 3 R
			dark chr.	4190 lm	105 lm/W	074-81265 3 B
		90	chrome	5100 lm	128 lm/W	074-81260 3 R
			dark chr.	3650 lm	91 lm/W	074-81260 3 B
	4000 K	80	chrome	6230 lm	156 lm/W	074-81266 3 R
			dark chr.	4460 lm	112 lm/W	074-81266 3 B
		90	chrome	5100 lm	128 lm/W	074-81261 3 R
			dark chr.	3650 lm	91 lm/W	074-81261 3 B

Optical accessories

BLIND COVER circle 240

ORDER CODE
074-89114 1

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

BLIND COVER circle 450

ORDER CODE
0 7 4 - 8 9 1 1 6 1

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

Endress+Hauser GmbH, Vienna

Austria

Arquitecto
FOKURA Luxury Interior,Reinhard Strempfl

Lighting Design
Ing. Gerhard Heil, TB Heil & Schafzahl GmbH


Fotografía
Kurt Kuball



Productos utilizados



SONIC suspended



MITA circle 240 / 450 recessed



UNICO L4 / L6 recessed

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com






MESSWERT
+MEHRWERT