



COMBO

trim


EN Round luminaire housing in aluminium with trim; suitable for installation in plasterboard ceilings; suitable for ceiling thickness of 10-25 mm; surface powder coated; up to ø600 mm: installation without tools using snap spring closure; highly reflective coating of the PCB for improved efficiency; completely homogeneously illuminated, satinised or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable

ES Cuerpo redondo con marco fabricado en aluminio; apropiada para montaje en techos de yeso; para instalación en techos de 10-25 mm de grosor; superficie con recubrimiento de pintura en polvo; hasta ø 600 mm: sencilla instalación sin herramientas mediante un enganche elástico; recubrimiento altamente reflectante de la pletina para un mayor rendimiento; iluminación homogénea, con efecto opal o microprismático; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; convertidor externo para inserción en el techo, adecuado para cableado pasante

Quickinfo

3000 K, 4000 K, tunable white
 2700 - 6500 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 UGR ≤ 19
 hasta 146 lm/W
 L90 / 50000 h
 DALI-2, non atenuable
 Microprismatic, Opal
 IP40

Types



Color



Distribución luminosa





DiiA® standards
 251, 252, 253




DIN EN 12464-1
 UGR ≤ 19





tunable white
 2700 – 6500 K

**COMBO 300 trim****MICROPRISMATIC** pure white, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
9.2 W	3000 K	979 lm	106 lm/W	0 6 4 - 1 0 3 1 5 \blacklozenge 7 K
	4000 K	1040 lm	113 lm/W	0 6 4 - 1 0 3 1 6 \blacklozenge 7 K
10.1 W	tunable w.	1050 lm	104 lm/W	0 6 4 - 1 0 3 1 D 3 7 K

**OPAL** pure white, CRI ≥ 80



SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
9.2 W	3000 K	993 lm	108 lm/W	0 6 4 - 1 0 3 1 5 \blacklozenge 7 O
	4000 K	1050 lm	114 lm/W	0 6 4 - 1 0 3 1 6 \blacklozenge 7 O
10.1 W	tunable w.	1060 lm	105 lm/W	0 6 4 - 1 0 3 1 D 3 7 O

**COMBO 450 trim****MICROPRISMATIC** pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.7 W	3000 K	2060 lm	123 lm/W	0 6 4 - 1 0 4 1 5 \blacklozenge 7 K
	4000 K	2180 lm	131 lm/W	0 6 4 - 1 0 4 1 6 \blacklozenge 7 K
18.0 W	tunable w.	2170 lm	121 lm/W	0 6 4 - 1 0 4 1 D 3 7 K

**OPAL** pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.7 W	3000 K	2050 lm	123 lm/W	0 6 4 - 1 0 4 1 5 \blacklozenge 7 O
	4000 K	2170 lm	130 lm/W	0 6 4 - 1 0 4 1 6 \blacklozenge 7 O
18.0 W	tunable w.	2150 lm	119 lm/W	0 6 4 - 1 0 4 1 D 3 7 O

**COMBO 600 trim****MICROPRISMATIC** pure white, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
30.0 W	3000 K	4060 lm	135 lm/W	0 6 4 - 1 0 5 1 5 \blacklozenge 7 K
	4000 K	4300 lm	143 lm/W	0 6 4 - 1 0 5 1 6 \blacklozenge 7 K
34.0 W	tunable w.	4420 lm	130 lm/W	0 6 4 - 1 0 5 1 D 3 7 K

**Order options**


CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		

OPAL pure white, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
30.0 W	3000 K	4020 lm	134 lm/W	0 6 4 - 1 0 5 1 5 \blacktriangleleft 7 0
	4000 K	4250 lm	142 lm/W	0 6 4 - 1 0 5 1 6 \blacktriangleleft 7 0
34.0 W	tunable w.	4370 lm	129 lm/W	0 6 4 - 1 0 5 1 D 3 7 0

**COMBO 900** trim**MICROPRISMATIC** pure white, CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
56.0 W	3000 K	7460 lm	133 lm/W	0 6 4 - 1 0 7 1 5 3 7 K
	4000 K	7900 lm	141 lm/W	0 6 4 - 1 0 7 1 6 3 7 K
60.0 W	tunable w.	7700 lm	128 lm/W	0 6 4 - 1 0 7 1 D 3 7 K

**OPAL** pure white, CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
56.0 W	3000 K	7440 lm	133 lm/W	0 6 4 - 1 0 7 1 5 3 7 0
	4000 K	7880 lm	141 lm/W	0 6 4 - 1 0 7 1 6 3 7 0
60.0 W	tunable w.	7670 lm	128 lm/W	0 6 4 - 1 0 7 1 D 3 7 0

**COMBO 1200** trim**MICROPRISMATIC** pure white, CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
92.0 W	3000 K	12600 lm	137 lm/W	0 6 4 - 1 0 8 1 5 3 7 K
	4000 K	13300 lm	145 lm/W	0 6 4 - 1 0 8 1 6 3 7 K
103.0 W	tunable w.	13500 lm	131 lm/W	0 6 4 - 1 0 8 1 D 3 7 K

**OPAL** pure white, CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
92.0 W	3000 K	12600 lm	137 lm/W	0 6 4 - 1 0 8 1 5 3 7 0
	4000 K	13400 lm	146 lm/W	0 6 4 - 1 0 8 1 6 3 7 0
103.0 W	tunable w.	13500 lm	131 lm/W	0 6 4 - 1 0 8 1 D 3 7 0


Mounting accessories (optional)**FALL PROTECTION**

TYPE	ORDER CODE
3 pieces	0 6 4 - 1 9 0 7 5 0 0

for COMBO 300 / 450 / 600

Order options

CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		

**MOUNTING RING 1200**

TYPE
for acoustic ceiling
for COMBO 1200

ORDER CODE


0 6 4 - 1 9 0 6 8 0 0

**MOUNTING RING 300**

TYPE
for acoustic ceiling
for COMBO 300

ORDER CODE


0 6 4 - 1 9 0 6 3 0 0

**MOUNTING RING 450**

TYPE
for acoustic ceiling
for COMBO 450

ORDER CODE


0 6 4 - 1 9 0 6 4 0 0

**MOUNTING RING 600**

TYPE
for acoustic ceiling
for COMBO 600

ORDER CODE

0 6 4 - 1 9 0 6 5 0 0

**MOUNTING RING 900**

TYPE
for acoustic ceiling
for COMBO 900

ORDER CODE

0 6 4 - 1 9 0 6 7 0 0

Order options**CONTROL**

non DIM
DALI-2

**COLOUR**

pure white

RAL 9010

1
3

Hargassner Energy World, Weng im Innkreis

Austria


Arquitecto
architekten
berger.hofmann og,
tech3
Projektentwicklung
GmbH

Lighting Design
AREA C.I.DESIGN GmbH

Fotografía
raumpixel.at



Productos utilizados




COMBO trim



MOVE IN round
recessed



JUST 45 MOVE IT
25 / 25 S / 45



MOVE IT 25 trimless
system

