

Quickinfo

3000 K, 4000 K, tunable white
2700 - 5000 K
CRI ≥ 90, CRI ≥ 97 / 3 SDCM (initial MacAdam)
hasta ↓ 4.020 lm/ ↑ 4.780 lm
hasta 125 lm/W
L85 / 50000 h, L95 / 50000 h
DALI-2, non atenuable
Opal, Opal / Asymmetric
IP20 / CP1 / 220-240 V
306 mm, 606 mm, 633 mm, 637 mm, 706 mm, 1.206 mm, 1.306 mm, 2.406 mm, 2.506 mm,

Types



Distribución luminosa



LINEA

system

EN Luminaire housing and front cover from extruded aluminium profile, angular version; no visible screws; designed for continuous lighting systems, 90° angle connectors for flexible system design; surface powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; opal cover for uniform illumination; or with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); energy-efficient LEDs with very good colour rendering; optionally JUST 26 spotlight module can be installed

ES Cuerpo de lámpara y cubierta frontal de perfil extrusionado de aluminio, versión poligonal; sin tornillos visibles; diseñado para sistemas de iluminación continuos, conectores angulares de 90° para el montaje flexible del sistema; superficie con recubrimiento de pintura en polvo; apropiada para montaje pared; iluminación homogénea de la pared o bien del techo mediante distribución uniforme directa/indirecta de la luz; cubierta opal para iluminación homogénea; o con lente asimétrica de cálculo especial para intensidades luminosas homogéneas (montaje para la iluminación del suelo o del techo); LEDS de alta eficiencia que proporcionan una alta reproducción cromática; compatible con inserto de foco JUST 26



CRI ≥ 98
XPECTRUM
(optional)



LINEA wall system

TUNABLE WHITE | CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↧428/↥509 lm	105 lm/W	058-614156 AA
		4000 K	↧472/↥562 lm	116 lm/W	058-614166 AA
17.6 W	606 mm	3000 K	↧881/↥1050 lm	110 lm/W	058-614256 AA
		4000 K	↧972/↥1160 lm	121 lm/W	058-614266 AA
34.0 W	1206 mm	3000 K	↧1760/↥2090 lm	113 lm/W	058-614456 AA
		4000 K	↧1940/↥2310 lm	125 lm/W	058-614466 AA
37.0 W	1206 mm	tunable w.	↧2010/↥2390 lm	119 lm/W	058-6144D3 AA
68.0 W	2406 mm	3000 K	↧3520/↥4190 lm	113 lm/W	058-614856 AA
		4000 K	↧3890/↥4620 lm	125 lm/W	058-614866 AA
71.0 W	2406 mm	tunable w.	↧4020/↥4780 lm	124 lm/W	058-6148D3 AA



OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↧428/↥428 lm	96 lm/W	058-614156 AH
		4000 K	↧472/↥472 lm	106 lm/W	058-614166 AH
17.6 W	606 mm	3000 K	↧881/↥881 lm	100 lm/W	058-614256 AH
		4000 K	↧972/↥972 lm	110 lm/W	058-614266 AH
34.0 W	1206 mm	3000 K	↧1760/↥1760 lm	104 lm/W	058-614456 AH
		4000 K	↧1940/↥1940 lm	114 lm/W	058-614466 AH
37.0 W	1206 mm	tunable w.	↧2010/↥2010 lm	109 lm/W	058-6144D3 AH
68.0 W	2406 mm	3000 K	↧3520/↥3520 lm	104 lm/W	058-614856 AH
		4000 K	↧3890/↥3890 lm	114 lm/W	058-614866 AH
71.0 W	2406 mm	tunable w.	↧4020/↥4020 lm	113 lm/W	058-6148D3 AH



LINEA inner corner wall system

TUNABLE WHITE | CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↧1760/↥2090 lm	113 lm/W	058-611156 AA
		4000 K	↧1940/↥2310 lm	125 lm/W	058-611166 AA
37.0 W	633 mm	tunable w.	↧2010/↥2390 lm	119 lm/W	058-6111D3 AA



Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8

OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↧1760/↥1760 lm	104 lm/W	0 5 8 - 6 1 1 1 5 ◆ ◪ A H
		4000 K	↧1940/↥1940 lm	114 lm/W	0 5 8 - 6 1 1 1 6 ◆ ◪ A H
37.0 W	633 mm	tunable w.	↧2010/↥2010 lm	109 lm/W	0 5 8 - 6 1 1 1 D 3 ◪ A H



LINEA outer corner wall system

TUNABLE WHITE · CRI ≥ 90 · 220-240 V · 1 ADDR. · X-PERT · X-PERT



OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↧1760/↥2090 lm	113 lm/W	0 5 8 - 6 1 1 2 5 ◆ ◪ A A
		4000 K	↧1940/↥2310 lm	125 lm/W	0 5 8 - 6 1 1 2 6 ◆ ◪ A A
37.0 W	637 mm	tunable w.	↧2010/↥2390 lm	119 lm/W	0 5 8 - 6 1 1 2 D 3 ◪ A A

OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↧1760/↥1760 lm	104 lm/W	0 5 8 - 6 1 1 2 5 ◆ ◪ A H
		4000 K	↧1940/↥1940 lm	114 lm/W	0 5 8 - 6 1 1 2 6 ◆ ◪ A H
37.0 W	637 mm	tunable w.	↧2010/↥2010 lm	109 lm/W	0 5 8 - 6 1 1 2 D 3 ◪ A H



LINEA 1 spotlight wall system

TUNABLE WHITE · CRI ≥ 90 · 220-240 V · 1 ADDR. · X-PERT · X-PERT



OPAL / OPAL | 1 SPOTLIGHT 30°, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.6 W	706 mm	3000 K	↧881/↥881 lm	100 lm/W	0 5 8 - 6 1 4 2 5 ◆ ◪ ♁ H
		4000 K	↧972/↥972 lm	110 lm/W	0 5 8 - 6 1 4 2 6 ◆ ◪ ♁ H
34.0 W	1306 mm	3000 K	↧1760/↥1760 lm	104 lm/W	0 5 8 - 6 1 4 4 5 ◆ ◪ ♁ H
		4000 K	↧1940/↥1940 lm	114 lm/W	0 5 8 - 6 1 4 4 6 ◆ ◪ ♁ H
37.0 W	1306 mm	tunable w.	↧2010/↥2010 lm	109 lm/W	0 5 8 - 6 1 4 4 D 3 ◪ ♁ H
68.0 W	2506 mm	3000 K	↧3520/↥3520 lm	104 lm/W	0 5 8 - 6 1 4 8 5 ◆ ◪ ♁ H
		4000 K	↧3890/↥3890 lm	114 lm/W	0 5 8 - 6 1 4 8 6 ◆ ◪ ♁ H
71.0 W	2506 mm	tunable w.	↧4020/↥4020 lm	113 lm/W	0 5 8 - 6 1 4 8 D 3 ◪ ♁ H

spotlight 1 x 2,6 W / 159 lm only with 3000 K

Mounting accessories



END CAPS 1 pair

L·W·H (mm)	ORDER CODE
40·100·12	0 5 0 - 2 5 4 0 1 0 ◪

Order options

CONTROL ◆		COLOUR ◪		MOUNTING ♁	
non DIM	1	pure white RAL 9010	7	spotlight left	B
DALI-2	3	jet black RAL 9005	8	spotlight right	C



LINEAR CONNECTOR

TYPE	L·W (mm)	ORDER CODE
1 piece	60·38	050-2551100
10 pieces	60·38	050-2551100·10

Electrical accessories

THROUGH WIRE

TYPE	ORDER CODE
3×1.5 mm² | 10 pieces | non DIM	004-90003
5×1.5 mm² | 10 pieces | DALI-2	004-90005