

Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 13, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
hasta ↓ 4.750 lm / ↑ 4.380 lm
hasta 163 lm/W
L90 / 100000 h, L90 / 75000 h
Difusor: Opal, Reflector
DALI-2
IP20

Types



Colours



Reflector



Distribución luminosa





dark chrome reflector option



up to 139 lm/W (high efficiency)



version with opal cover



magnetic blind cover



DIN EN 12464-1 UGR ≤ 19

MITA circle 450

suspended

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; opal cover for uniform illumination; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering

ES Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; superficie con recubrimiento de pintura en polvo; suspendido; con suspensión acortable de tubo pendular (cromo), línea de alimentación en tubo pendular; driver instalado en el baldaquino; opcional: cubierta opaca de fijación a recorte de techo con imán disponible como accesorio adicional; reflector de alto brillo con óptica facetada; cubierta opal para iluminación homogénea; opcionalmente con característica de emisión directa o directa/indirecta; LEDS de alta eficiencia que proporcionan una alta reproducción cromática





MITA circle 450 reflector suspended

CRI ≥ 90 | UGR ≤ 13 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT

DIRECT | REFLECTOR (UGR ≤ 19) DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
29.4 W	3000 K	80	chrome	4500 lm	153 lm/W	074-761153 R
			dark chr.	3220 lm	110 lm/W	074-761153 B
		90	chrome	3920 lm	133 lm/W	074-761103 R
			dark chr.	2800 lm	95 lm/W	074-761103 B
	4000 K	80	chrome	4790 lm	163 lm/W	074-761163 R
			dark chr.	3430 lm	117 lm/W	074-761163 B
		90	chrome	3920 lm	133 lm/W	074-761113 R
			dark chr.	2800 lm	95 lm/W	074-761113 B
40.0 W	3000 K	80	chrome	5850 lm	146 lm/W	074-762153 R
			dark chr.	4190 lm	105 lm/W	074-762153 B
		90	chrome	5100 lm	128 lm/W	074-762103 R
			dark chr.	3650 lm	91 lm/W	074-762103 B
	4000 K	80	chrome	6230 lm	156 lm/W	074-762163 R
			dark chr.	4460 lm	112 lm/W	074-762163 B
		90	chrome	5100 lm	128 lm/W	074-762113 R
			dark chr.	3650 lm	91 lm/W	074-762113 B

DIRECT / INDIRECT POWER | REFLECTOR (UGR ≤ 19) DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
58.0 W	3000 K	80	chrome	↧4460/↥3850 lm	143 lm/W	074-765153 R
			dark chr.	↧3180/↥3850 lm	121 lm/W	074-765153 B
		90	chrome	↧3880/↥3320 lm	124 lm/W	074-765103 R
			dark chr.	↧2770/↥3320 lm	105 lm/W	074-765103 B
	4000 K	80	chrome	↧4750/↥4380 lm	157 lm/W	074-765163 R
			dark chr.	↧3380/↥4380 lm	134 lm/W	074-765163 B
		90	chrome	↧3880/↥3580 lm	129 lm/W	074-765113 R
			dark chr.	↧2770/↥3580 lm	109 lm/W	074-765113 B

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8





MITA circle 450 opal suspended

CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL | DIRECT DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
24.9 W	3000 K	80	2950 lm	118 lm/W	074-761153 ◪ O
		90	2570 lm	103 lm/W	074-761103 ◪ O
	4000 K	80	3140 lm	126 lm/W	074-761163 ◪ O
		90	2570 lm	103 lm/W	074-761113 ◪ O

OPAL | DIRECT / INDIRECT POWER DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
58.0 W	3000 K	80	↧3580/↥3850 lm	128 lm/W	074-765153 ◪ O
		90	↧3120/↥3320 lm	111 lm/W	074-765103 ◪ O
	4000 K	80	↧3810/↥4380 lm	141 lm/W	074-765163 ◪ O
		90	↧3110/↥3580 lm	115 lm/W	074-765113 ◪ O

Optical accessories

BLIND COVER circle 450 ceiling

Ø (mm)	ORDER CODE
339	074-891162 ◪

Order options

COLOUR ◪	
traffic white RAL 9016	7
jet black RAL 9005	8