



Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
hasta 139 lm/W
L80 / 50000 h
DALI-2, non atenuable
IP20

Types



Colours

Distribución luminosa

SQUADRO wallwasher

track 2 lamps

EN Track light in die cast aluminium in two different types (2 lamps or 2x2 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); surface powder coated; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP40 protection glass available as an accessory; including attachment for linear alignment of the spotlights

ES Proyector en raíl electrificado de fundición de aluminio en 2 diferentes variantes (de 2 lámparas o bien de 2x2 lámparas) y con 2 módulos de iluminación diferentes (para shelf floor washer und wall floor washer); superficie con recubrimiento de pintura en polvo; Proyector para zonas de pasillos con reflectores especiales de múltiples superficies de formas libres con óptica faceteada para una orientación de la luz sumamente precisa; iluminación precisa de estanterías y de zonas de pasillos, evitando de forma óptima el deslumbramiento longitudinal para un elevado confort visual en la zona del pasillo, módulos de iluminación ajustables; Chip on Board que proporciona una máxima eficiencia; LEDS de eficiencia que proporcionan una alta reproducción cromática; vidrio de protección IP 40 disponible como accesorio; incluye accesorio para la correcta alineación de la luminaria




DiiA® standards 251, 252, 253



up to 139 lm/W (high efficiency)




glare-free reflector longitudinally & transversely




+20° up to -15° tiltable









SQUADRO single-sided wallwasher track

30° 350° | CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT


SHELF FLOOR WASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	3000 K	4910 lm	136 lm/W	1 4 9 - 2 2 1 0 0 ◆ ◪ S
	3500 K	4970 lm	138 lm/W	1 4 9 - 2 2 1 0 2 ◆ ◪ S
	4000 K	4980 lm	138 lm/W	1 4 9 - 2 2 1 0 1 ◆ ◪ S

WALL FLOOR WASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	3000 K	4920 lm	137 lm/W	1 4 9 - 2 2 1 0 0 ◆ ◪ A
	3500 K	4980 lm	138 lm/W	1 4 9 - 2 2 1 0 2 ◆ ◪ A
	4000 K	4990 lm	139 lm/W	1 4 9 - 2 2 1 0 1 ◆ ◪ A





SQUADRO double-sided wallwasher track

30° 350° | CRI ≥ 90 | 2 SDCM | 220-240 V | X-PERT | X-PERT

SHELF FLOOR WASHER CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
72.0 W	3000 K	9820 lm	136 lm/W	1 4 9 - 2 2 2 0 0 1 ◪ S
	3500 K	9940 lm	138 lm/W	1 4 9 - 2 2 2 0 2 1 ◪ S
	4000 K	9960 lm	138 lm/W	1 4 9 - 2 2 2 0 1 1 ◪ S

WALL FLOOR WASHER CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
72.0 W	3000 K	9830 lm	137 lm/W	1 4 9 - 2 2 2 0 0 1 ◪ A
	3500 K	9950 lm	138 lm/W	1 4 9 - 2 2 2 0 2 1 ◪ A
	4000 K	9970 lm	138 lm/W	1 4 9 - 2 2 2 0 1 1 ◪ A

1×SHELF / 1×WALL FLOOR WASHER CRI ≥ 90, non DIM


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
72.0 W	3000 K	9830 lm	137 lm/W	1 4 9 - 2 2 2 0 0 1 ◪ B
	3500 K	9950 lm	138 lm/W	1 4 9 - 2 2 2 0 2 1 ◪ B
	4000 K	9970 lm	138 lm/W	1 4 9 - 2 2 2 0 1 1 ◪ B

Order options


CONTROL ◆		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Planning Information

SQUADRO 1×2 lamps, shelf wall washer, trim, 36 W, 3000 K



SQUADRO 1×2 lamps, wall floor washer, trim, 36 W, 3000 K



ROOM VALUES	
Wall dimensions	H = 3.5 m | W = 10.8 m
Distance to wall	B = 1.3 m
Aisle width	2.6 m
Reflection factor	0.7 | 0.7 | 0.2
Maintenance factor	0.9

CALCULATION SURFACE	
Surface dimensions	10.8 × 3.5 m
Surface height	0 – 3.5 m
Eye level	1.35 m – 1.75 m

Optical accessories

IP40 PROTECTION GLASS

TYPE	ORDER CODE
1 x 2 lamps / single-sided	049-291001 0
2 x 2 lamps / double-sided	049-292001 0