

MINO 60 S CIRCLE

suspended


EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; HPO (High Performance Opal) cover for uniform illumination; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering

ES Luminaria con forma de anillo fabricada en aluminio con soldadura de alta calidad; Luminaria extra plana; superficie con recubrimiento de pintura en polvo; suspendido con cable, opcionalmente con baldaquino central; altura regulable sin herramientas; incl. cable de alimentación (negro o blanco); convertidor integrado en el baldaquino; difusor opal de alta calidad que proporciona una iluminación uniforme; opcionalmente iluminación directa/indirecta para proporcionar un alto confort visual; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
 CRI \geq 80 / 3 SDCM (initial MacAdam)
 hasta 10,300 lm / 1 5,800 lm
 hasta 137 lm/W
 L90 / 100000 h
 DALI-2
 High Performance Opal
 IP20

Types



Color




Distribución luminosa




DiiA® standards
 251, 252, 253



direct / indirect
 illumination



*direct/indirect version



*direct/indirect version

MINO 60 S circle 1000 suspended




OPAL | DIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
59.0 W	3000 K	6860 lm	116 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 2 5 3 <input checked="" type="checkbox"/> H
	4000 K	7300 lm	124 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 2 6 3 <input checked="" type="checkbox"/> H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
79.0 W	3000 K	↓6860/↑3120 lm	126 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 3 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓7300/↑3550 lm	137 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 3 6 3 <input checked="" type="checkbox"/> H



*direct/indirect version



*direct/indirect version

MINO 60 S circle 1500 suspended



OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	9630 lm	116 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 0 5 3 <input checked="" type="checkbox"/> H
	4000 K	10300 lm	124 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 0 6 3 <input checked="" type="checkbox"/> H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
119.0 W	3000 K	↓9630/↑5100 lm	124 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 1 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓10300/↑5800 lm	135 lm/W	0 3 4 - 7 <input type="checkbox"/> 1 1 6 3 <input checked="" type="checkbox"/> H

Order options

MOUNTING		COLOUR	
cable 1500 mm	2	white aluminium RAL 9006	G
cable 1500 mm / canopy central	4	special colours	X
		pure white RAL 9010	7
		jet black RAL 9005	8

Dentsu Aegis Network, Zurich

Suiza

Arquitecto
Büronauten AG

Lighting Design
Caduff Socker

Fotografía
Z. Gataric Fotografie



Productos utilizados



MINO 60 CIRCLE
suspended



TULA suspended



**TULA MOVE IT 25 /
25 S / 45**



MINO 60 S CIRCLE
suspended

