


## Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
hasta ↓ 10.300 lm / ↑ 5.800 lm
hasta 137 lm/W
L90 / 100000 h
Difusor: Opal
DALI-2
IP20

### Types




### Colours

### Distribución luminosa

# MINO 60 S CIRCLE

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; opal cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering

ES Luminaria con forma de anillo fabricada en aluminio con soldadura de alta calidad; Luminaria extra plana; superficie con recubrimiento de pintura en polvo; suspendido con cable, opcionalmente con baldaquino central; altura regulable sin herramientas; incl. cable de alimentación (negro o blanco); convertidor integrado en el baldaquino; cubierta opal para iluminación homogénea; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminancia y un alumbrado homogéneo; opcionalmente iluminación directa/indirecta para proporcionar un alto confort visual; LEDS de alta eficiencia que proporcionan una alta reproducción cromática





DiiA® standards 251, 252, 253




direct / indirect illumination








*direct/indirect version




*direct/indirect version

## **MINO 60 S** circle 1000 suspended

CRI ≥ 80 | 220-240 V | 1-2 ADDR. | X-PERT | X-PERT

**OPAL | DIRECT** CRI ≥ 80, DALI-2


| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 59.0 W | 3000 K | 6860 lm | 116 lm/W | 0 3 4 - 7 ♁ 1 2 5 3 ◪ H |
| | 4000 K | 7300 lm | 124 lm/W | 0 3 4 - 7 ♁ 1 2 6 3 ◪ H |

**OPAL | DIRECT / INDIRECT** CRI ≥ 80, DALI-2


| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 79.0 W | 3000 K | ↧6860/↥3120 lm | 126 lm/W | 0 3 4 - 7 ♁ 1 3 5 3 ◪ H |
| | 4000 K | ↧7300/↥3550 lm | 137 lm/W | 0 3 4 - 7 ♁ 1 3 6 3 ◪ H |








*direct/indirect version




*direct/indirect version

## **MINO 60 S** circle 1500 suspended

CRI ≥ 80 | UGR ≤22 | 220-240 V | 1-5 ADDR. | X-PERT | X-PERT

**OPAL | DIRECT** CRI ≥ 80, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 83.0 W | 3000 K | 9630 lm | 116 lm/W | 0 3 4 - 7 ♁ 1 0 5 3 ◪ H |
| | 4000 K | 10300 lm | 124 lm/W | 0 3 4 - 7 ♁ 1 0 6 3 ◪ H |

**OPAL | DIRECT / INDIRECT** CRI ≥ 80, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 119.0 W | 3000 K | ↧9630/↥5100 lm | 124 lm/W | 0 3 4 - 7 ♁ 1 1 5 3 ◪ H |
| | 4000 K | ↧10300/↥5800 lm | 135 lm/W | 0 3 4 - 7 ♁ 1 1 6 3 ◪ H |

### Order options

| MOUNTING | ♁ |
|---|---|
| cable 1500 mm | 2 |
| cable 1500 mm / canopy central | 4 |

| COLOUR | ◪ |
|---|---|
| pure white RAL 9010 | 7 |
| jet black RAL 9005 | 8 |
| white aluminium RAL 9006 | G |
| special colours | X |

# Dentsu Aegis Network, Zurich

Suiza

**Arquitecto**
Büronauten AG

**Lighting Design**
Caduff Socker

**Fotografía**
Z. Gataric Fotografie



**Productos utilizados**



**MINO 60 CIRCLE suspended**



**TULA suspended**



**TULA MOVE IT 25 / 25 S / 45**



**MINO 60 S CIRCLE suspended**

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com







