

## MINO 60 S CIRCLE

suspended


**EN** Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; HPO (High Performance Opal) cover for uniform illumination; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering

**ES** Luminaria con forma de anillo fabricada en aluminio con soldadura de alta calidad; Luminaria extra plana; superficie con recubrimiento de pintura en polvo; suspendido con cable, opcionalmente con baldaquino central; altura regulable sin herramientas; incl. cable de alimentación (negro o blanco); convertidor integrado en el baldaquino; difusor opal de alta calidad que proporciona una iluminación uniforme; opcionalmente iluminación directa/indirecta para proporcionar un alto confort visual; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

3000 K, 4000 K  
CRI  $\geq$  80 / 3 SDCM  
hasta  $\downarrow$  10,300 lm /  $\uparrow$  5,800 lm  
hasta 137 lm/W  
L90 / 50000 h  
DALI-2  
High Performance Opal  
IP20

### Types



### Color




### Distribución luminosa




DiiA® standards  
251, 252, 253



direct / indirect  
illumination



\*direct/indirect version



\*direct/indirect version

### MINO 60 S CIRCLE 1000 suspended





#### OPAL | DIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
59.0 W	3000 K	6420 lm	109 lm/W	0 3 4 - 7 8 1 2 5 3 H
	4000 K	7300 lm	124 lm/W	0 3 4 - 7 8 1 2 6 3 H

#### OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
79.0 W	3000 K	↓6420/↑3120 lm	121 lm/W	0 3 4 - 7 8 1 3 5 3 H
	4000 K	↓7300/↑3550 lm	137 lm/W	0 3 4 - 7 8 1 3 6 3 H



\*direct/indirect version



\*direct/indirect version

### MINO 60 S CIRCLE 1500 suspended



#### OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	9010 lm	109 lm/W	0 3 4 - 7 8 1 0 5 3 H
	4000 K	10300 lm	124 lm/W	0 3 4 - 7 8 1 0 6 3 H

#### OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
119.0 W	3000 K	↓9010/↑5100 lm	119 lm/W	0 3 4 - 7 8 1 1 5 3 H
	4000 K	↓10300/↑5800 lm	135 lm/W	0 3 4 - 7 8 1 1 6 3 H

#### Order options

MOUNTING		COLOUR	
cable 1500 mm	2	pure white RAL 9010	7
cable 1500 mm / canopy central	4	jet black RAL 9005	8
		white aluminium RAL 9006	G
		special colours	X

# Dentsu Aegis Network, Zurich

Suiza

**Arquitecto**  
Büronauten AG

**Lighting Design**  
Caduff Socker

**Fotografía**  
Z. Gataric Fotografie



## Productos utilizados



**MINO 60 CIRCLE**  
suspended



**TULA suspended**



**TULA MOVE IT 25 /  
25 S / 45**



**MINO 60 S CIRCLE**  
suspended







