


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
hasta 2.510 lm/m
hasta 113 lm/W
L85 / 50000 h
DALI-2, non atenuable
Opal
IP44

Types



Colours

Tapa terminal

Distribución luminosa

STRETTA


wall

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be premounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering

ES Perfil de aluminio extrusionado, versión angulosa; sin tornillos visibles; superficie con recubrimiento de pintura en polvo; perfil de luminaria premontable; tapas terminales en el color de la luminaria con recubrimiento de pintura en polvo o acabado de aluminio cepillado; apropiada para montaje pared; con proyección de luz por tres lados; cubierta opal para iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática


wall illumination


splash water protection (IP 44)


CRI ≥ 98 XPECTRUM





STRETTA wall

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-013256 ◆ ◪ H
		4000 K	1480 lm	113 lm/W	057-013266 ◆ ◪ H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-013356 ◆ ◪ H
		4000 K	2220 lm	113 lm/W	057-013366 ◆ ◪ H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-013456 ◆ ◪ H
		4000 K	2950 lm	112 lm/W	057-013466 ◆ ◪ H






STRETTA wall | end caps aluminium

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL pure white, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-013256 ◆ 2 H
		4000 K	1480 lm	113 lm/W	057-013266 ◆ 2 H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-013356 ◆ 2 H
		4000 K	2220 lm	113 lm/W	057-013366 ◆ 2 H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-013456 ◆ 2 H
		4000 K	2950 lm	112 lm/W	057-013466 ◆ 2 H



Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8