



STRETTA

wall


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

ES Perfil de aluminio extrusionado, versión angular; sin tornillos visibles; superficie con recubrimiento de pintura en polvo; perfil de luminaria premontable; tapas terminales en el color de la luminaria con recubrimiento de pintura en polvo o acabado de aluminio cepillado; apropiada para montaje pared; con proyección de luz por tres lados; tapa HPO (High Performance Opal) para iluminación homogénea; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 hasta 2,510 lm/m
 hasta 113 lm/W
 L80 / 50000 h
 DALI-2, non atenuable
 High Performance Opal
 IP44

Types



Color



Tapa terminal




Distribución luminosa



wall illumination



splash water protection (IP44)



CRI \geq 98 XPECTRUM




STRETTA wall



OPAL CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------|-----------|----------|---------------------------------------------------------|
| 13.1 W | 600 mm | 3000 K | 1340 lm | 102 lm/W | 0 5 7 - 0 1 3 2 5 <input checked="" type="checkbox"/> H |
| | | 4000 K | 1480 lm | 113 lm/W | 0 5 7 - 0 1 3 2 6 <input checked="" type="checkbox"/> H |
| 19.7 W | 900 mm | 3000 K | 2010 lm | 102 lm/W | 0 5 7 - 0 1 3 3 5 <input checked="" type="checkbox"/> H |
| | | 4000 K | 2220 lm | 113 lm/W | 0 5 7 - 0 1 3 3 6 <input checked="" type="checkbox"/> H |
| 26.3 W | 1200 mm | 3000 K | 2680 lm | 102 lm/W | 0 5 7 - 0 1 3 4 5 <input checked="" type="checkbox"/> H |
| | | 4000 K | 2950 lm | 112 lm/W | 0 5 7 - 0 1 3 4 6 <input checked="" type="checkbox"/> H |




STRETTA wall | end caps aluminium



OPAL pure white, CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------|-----------|----------|-----------------------------------------------------------|
| 13.1 W | 600 mm | 3000 K | 1340 lm | 102 lm/W | 0 5 7 - 0 1 3 2 5 <input checked="" type="checkbox"/> 2 H |
| | | 4000 K | 1480 lm | 113 lm/W | 0 5 7 - 0 1 3 2 6 <input checked="" type="checkbox"/> 2 H |
| 19.7 W | 900 mm | 3000 K | 2010 lm | 102 lm/W | 0 5 7 - 0 1 3 3 5 <input checked="" type="checkbox"/> 2 H |
| | | 4000 K | 2220 lm | 113 lm/W | 0 5 7 - 0 1 3 3 6 <input checked="" type="checkbox"/> 2 H |
| 26.3 W | 1200 mm | 3000 K | 2680 lm | 102 lm/W | 0 5 7 - 0 1 3 4 5 <input checked="" type="checkbox"/> 2 H |
| | | 4000 K | 2950 lm | 112 lm/W | 0 5 7 - 0 1 3 4 6 <input checked="" type="checkbox"/> 2 H |



Order options

| CONTROL | | COLOUR | |
|---------|---|---------------------|---|
| non DIM | 1 | pure white RAL 9010 | 7 |
| DALI-2 | 3 | jet black RAL 9005 | 8 |