


Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 97 / 3 SDCM (initial MacAdam)
hasta 1.290 lm/m
hasta 81 lm/W
L85 / 50000 h
driver no incluido
Opal
IP20

Types



Colours

Distribución luminosa

FINA SUPPORT opal

standing system

EN Miniature rectangular lamp made of aluminium; angular design; surface lacquered; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available; for flexible system design; completely homogeneously illuminated, satinised PMMA cover; light inset rotatable; energy-efficient LEDs with very good colour rendering; converter plug and play; converter separately available

ES Miniluminaria rectangular de aluminio; forma angulosa; superficie lacada; sistema de conexión eléctrico metalizado para un montaje sin herramientas; diferentes postes mecánicos y eléctricos disponibles; para el montaje flexible del sistema; tapa PMMA iluminada homogéneamente con acabado sanitado; elemento de luz giratorio; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; convertidor prefabricado listo para enchufar; el convertidor debe encargarse por separado



CRI ≥ 95, R9 ≥ 90



seamless design



360° tiltable





FINA SUPPORT OPAL STANDING SYSTEM

360° | CRI ≥ 97 | 24V | DALI-2 | CB | X-PERT

OPAL CRI ≥ 97, excl. driver

FIXTURE	LENGTH	LUM. FLUX	ORDER CODE
1.5 W	100 mm	84 lm	0 1 1 - 1 2 0 1 :: 1 ◪ O
2.0 W	135 mm	124 lm	0 1 1 - 1 2 9 A C :: 1 ◪ O
2.7 W	170 mm	165 lm	0 1 1 - 1 2 9 A D :: 1 ◪ O
3.3 W	205 mm	206 lm	0 1 1 - 1 2 9 A E :: 1 ◪ O
3.6 W	200 mm	223 lm	0 1 1 - 1 2 0 2 :: 1 ◪ O
4.0 W	240 mm	247 lm	0 1 1 - 1 2 9 A F :: 1 ◪ O
4.7 W	275 mm	288 lm	0 1 1 - 1 2 9 A G :: 1 ◪ O
5.3 W	310 mm	330 lm	0 1 1 - 1 2 9 A H :: 1 ◪ O
6.0 W	345 mm	371 lm	0 1 1 - 1 2 9 A I :: 1 ◪ O
6.7 W	380 mm	412 lm	0 1 1 - 1 2 9 A J :: 1 ◪ O
7.3 W	400 mm	446 lm	0 1 1 - 1 2 0 3 :: 1 ◪ O
7.4 W	415 mm	453 lm	0 1 1 - 1 2 9 A K :: 1 ◪ O
8.0 W	450 mm	494 lm	0 1 1 - 1 2 9 A L :: 1 ◪ O
8.7 W	485 mm	536 lm	0 1 1 - 1 2 9 A M :: 1 ◪ O
9.4 W	520 mm	577 lm	0 1 1 - 1 2 9 A N :: 1 ◪ O
10.0 W	555 mm	618 lm	0 1 1 - 1 2 9 A O :: 1 ◪ O
10.6 W	590 mm	659 lm	0 1 1 - 1 2 9 A P :: 1 ◪ O
11.4 W	625 mm	700 lm	0 1 1 - 1 2 9 A Q :: 1 ◪ O
11.6 W	600 mm	714 lm	0 1 1 - 1 2 0 4 :: 1 ◪ O
12.0 W	660 mm	742 lm	0 1 1 - 1 2 9 A R :: 1 ◪ O
12.7 W	695 mm	783 lm	0 1 1 - 1 2 9 A S :: 1 ◪ O
13.4 W	730 mm	824 lm	0 1 1 - 1 2 9 A T :: 1 ◪ O
14.0 W	765 mm	865 lm	0 1 1 - 1 2 9 A U :: 1 ◪ O
14.6 W	800 mm	892 lm	0 1 1 - 1 2 0 5 :: 1 ◪ O
15.3 W	835 mm	947 lm	0 1 1 - 1 2 9 A W :: 1 ◪ O
16.1 W	870 mm	989 lm	0 1 1 - 1 2 9 A X :: 1 ◪ O
16.7 W	905 mm	1030 lm	0 1 1 - 1 2 9 A Y :: 1 ◪ O
17.3 W	940 mm	1070 lm	0 1 1 - 1 2 9 A Z :: 1 ◪ O
18.1 W	975 mm	1110 lm	0 1 1 - 1 2 9 B A :: 1 ◪ O
18.2 W	1000 mm	1110 lm	0 1 1 - 1 2 0 6 :: 1 ◪ O
18.7 W	1010 mm	1150 lm	0 1 1 - 1 2 9 B B :: 1 ◪ O
19.4 W	1045 mm	1190 lm	0 1 1 - 1 2 9 B C :: 1 ◪ O
20.1 W	1080 mm	1240 lm	0 1 1 - 1 2 9 B D :: 1 ◪ O
20.7 W	1115 mm	1280 lm	0 1 1 - 1 2 9 B E :: 1 ◪ O
21.4 W	1150 mm	1320 lm	0 1 1 - 1 2 9 B F :: 1 ◪ O
21.8 W	1200 mm	1340 lm	0 1 1 - 1 2 0 7 :: 1 ◪ O

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour temperature 4000 K, 3500 K. Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

Order options

COLOUR TEMPERATURE ::	
3000 K	0
4000 K	1
3500 K	2

COLOUR ◪	
white aluminium RAL 9006	6
tar black RAL 9021	8

NOTE

Products from the Showcase Lighting range are excluded from returns.





FINA SUPPORT OPAL 30° STANDING SYSTEM

360° | CRI ≥ 97 | 24V | DALI-2 | CB | UL | X-PERT

OPAL CRI ≥ 97, excl. driver

FIXTURE	LENGTH	LUM. FLUX	ORDER CODE
1.5 W	100 mm	84 lm	011-1301 :: 1 ◪ O
2.0 W	135 mm	124 lm	011-139AC :: 1 ◪ O
2.7 W	170 mm	165 lm	011-139AD :: 1 ◪ O
3.3 W	205 mm	206 lm	011-139AE :: 1 ◪ O
3.6 W	200 mm	223 lm	011-1302 :: 1 ◪ O
4.0 W	240 mm	247 lm	011-139AF :: 1 ◪ O
4.7 W	275 mm	288 lm	011-139AG :: 1 ◪ O
5.3 W	310 mm	330 lm	011-139AH :: 1 ◪ O
6.0 W	345 mm	371 lm	011-139AI :: 1 ◪ O
6.7 W	380 mm	412 lm	011-139AJ :: 1 ◪ O
7.3 W	400 mm	446 lm	011-1303 :: 1 ◪ O
7.4 W	415 mm	453 lm	011-139AK :: 1 ◪ O
8.0 W	450 mm	494 lm	011-139AL :: 1 ◪ O
8.7 W	485 mm	536 lm	011-139AM :: 1 ◪ O
9.4 W	520 mm	577 lm	011-139AN :: 1 ◪ O
10.0 W	555 mm	618 lm	011-139AO :: 1 ◪ O
10.6 W	590 mm	659 lm	011-139AP :: 1 ◪ O
11.4 W	625 mm	700 lm	011-139AQ :: 1 ◪ O
11.6 W	600 mm	714 lm	011-1304 :: 1 ◪ O
12.0 W	660 mm	742 lm	011-139AR :: 1 ◪ O
12.7 W	695 mm	783 lm	011-139AS :: 1 ◪ O
13.4 W	730 mm	824 lm	011-139AT :: 1 ◪ O
14.0 W	765 mm	865 lm	011-139AU :: 1 ◪ O
14.6 W	800 mm	892 lm	011-1305 :: 1 ◪ O
15.3 W	835 mm	947 lm	011-139AW :: 1 ◪ O
16.1 W	870 mm	989 lm	011-139AX :: 1 ◪ O
16.7 W	905 mm	1030 lm	011-139AY :: 1 ◪ O
17.3 W	940 mm	1070 lm	011-139AZ :: 1 ◪ O
18.1 W	975 mm	1110 lm	011-139BA :: 1 ◪ O
18.2 W	1000 mm	1110 lm	011-1306 :: 1 ◪ O
18.7 W	1010 mm	1150 lm	011-139BB :: 1 ◪ O
19.4 W	1045 mm	1190 lm	011-139BC :: 1 ◪ O
20.1 W	1080 mm	1240 lm	011-139BD :: 1 ◪ O
20.7 W	1115 mm	1280 lm	011-139BE :: 1 ◪ O
21.4 W	1150 mm	1320 lm	011-139BF :: 1 ◪ O
21.8 W	1200 mm	1340 lm	011-1307 :: 1 ◪ O

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour temperature 4000 K, 3500 K. Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

Order options


COLOUR TEMPERATURE ::	
3000 K	0
4000 K	1
3500 K	2

COLOUR ◪	
white aluminium RAL 9006	6
tar black RAL 9021	8

NOTE

Products from the Showcase Lighting range are excluded from returns.

Planning Information



1 **L-SUPPORT SQUARE** mechanical


2 **T-SUPPORT SQUARE** mechanical / electrical

2 **Y-SUPPORT SQUARE** mechanical / electrical

3 **L-SUPPORT SQUARE** mechanical / feeder


3 **Y-SUPPORT SQUARE** mechanical / feeder

Electrical mounting accessories



CONNECTION CABLE

TYPE	ORDER CODE
1 × open / 1 × DC plug	0 1 1 - 9 2 2 2 6 2 0




EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 2 1 2 0
2000 mm	0 1 1 - 9 2 2 2 1 4 0
4000 mm	0 1 1 - 9 2 2 2 1 8 0

FLEX CONNECTOR 0-83° electrical

L-W (mm)	ORDER CODE
33·6	0 1 1 - 9 2 2 5 4 0 0



MOUNTING POLE L mechanical / feeder

L (mm)	ORDER CODE
180	0 1 1 - 9 1 2 W 1 3 ◪
200	0 1 1 - 9 1 2 W 2 3 ◪
300	0 1 1 - 9 1 2 W 3 3 ◪

Order options


WIDTH	W
20 mm	1
35 mm	4
50 mm	5
85 mm	6

WIDTH	W
95 mm	7
100 mm	8

COLOUR	◪
white aluminium RAL 9006	6
tar black RAL 9021	8


NOTE

Products from the Showcase Lighting range are excluded from returns.




MOUNTING POLE T mechanical / electrical

L·W (mm)	ORDER CODE
180·31	0 1 1 - 9 1 2 2 1 2
200·31	0 1 1 - 9 1 2 2 2 2
300·31	0 1 1 - 9 1 2 2 3 2



MOUNTING POLE Y mechanical / electrical


L·W (mm)	ORDER CODE
180·24	0 1 1 - 9 1 2 3 1 2
200·24	0 1 1 - 9 1 2 3 2 2
300·24	0 1 1 - 9 1 2 3 3 2



MOUNTING POLE Y mechanical / feeder

L·W (mm)	ORDER CODE
180·24	0 1 1 - 9 1 2 3 1 3
200·24	0 1 1 - 9 1 2 3 2 3
300·24	0 1 1 - 9 1 2 3 3 3

Mounting accessories



MOUNTING POLE L mechanical

COLOUR	L·W (mm)	ORDER CODE
white aluminium	180·20	0 1 1 - 9 1 2 1 1 1 6
tar black	180·20	0 1 1 - 9 1 2 1 1 1 8
white aluminium	200·20	0 1 1 - 9 1 2 1 2 1 6
tar black	200·20	0 1 1 - 9 1 2 1 2 1 8
white aluminium	300·20	0 1 1 - 9 1 2 1 3 1 6
tar black	300·20	0 1 1 - 9 1 2 1 3 1 8
white aluminium	180·35	0 1 1 - 9 1 2 4 1 1 6
tar black	180·35	0 1 1 - 9 1 2 4 1 1 8
white aluminium	200·35	0 1 1 - 9 1 2 4 2 1 6
tar black	200·35	0 1 1 - 9 1 2 4 2 1 8
white aluminium	300·35	0 1 1 - 9 1 2 4 3 1 6
tar black	300·35	0 1 1 - 9 1 2 4 3 1 8
white aluminium	180·50	0 1 1 - 9 1 2 5 1 1 6
tar black	180·50	0 1 1 - 9 1 2 5 1 1 8
white aluminium	200·50	0 1 1 - 9 1 2 5 2 1 6
tar black	200·50	0 1 1 - 9 1 2 5 2 1 8
white aluminium	300·50	0 1 1 - 9 1 2 5 3 1 6
tar black	300·50	0 1 1 - 9 1 2 5 3 1 8
white aluminium	180·85	0 1 1 - 9 1 2 6 1 1 6
tar black	180·85	0 1 1 - 9 1 2 6 1 1 8
white aluminium	200·85	0 1 1 - 9 1 2 6 2 1 6
tar black	200·85	0 1 1 - 9 1 2 6 2 1 8
white aluminium	300·85	0 1 1 - 9 1 2 6 3 1 6
tar black	300·85	0 1 1 - 9 1 2 6 3 1 8

Order options

COLOUR	
white aluminium RAL 9006	6
tar black RAL 9021	8

NOTE

Products from the Showcase Lighting range are excluded from returns.

COLOUR	L·W (mm)	ORDER CODE
white aluminium	180·95	011-912711 6
tar black	180·95	011-912711 8
white aluminium	200·95	011-912721 6
tar black	200·95	011-912721 8
white aluminium	300·95	011-912731 6
tar black	300·95	011-912731 8
white aluminium	180·100	011-912811 6
tar black	180·100	011-912811 8
white aluminium	200·100	011-912821 6
tar black	200·100	011-912821 8
white aluminium	300·100	011-912831 6
tar black	300·100	011-912831 8

Electrical accessories

POWER SUPPLY 24V EU PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
18 W | non DIM	198-264 V AC	η 86 %	130·43·30	011-921211 0
35 W | non DIM	198-264 V AC	η 86 %	195·43·30	011-921221 0
60 W | non DIM	198-264 V AC	η 91 %	220·43·30	011-921231 0
18 W | DALI-2	198-264 V AC	η 84 %	130·43·30	011-921213 0
35 W | DALI-2	198-264 V AC	η 89 %	195·43·30	011-921223 0
60 W | DALI-2	198-240 V AC	η 93 %	220·43·30	011-921233 0

incl. power cable 2m + connection cable with plug 1m

POWER SUPPLY 24V UL non DIM, 100-305 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
25 W	η 88 %	147·40·32	011-927211 0
40 W	η 88 %	147·40·32	011-927221 0
60 W	η 87 %	176·45·32	011-927231 0

POWER SUPPLY 24V UL incl. metalbox non DIM, 100-305 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
25 W	η 88 %	196·68·45	011-929211 0
40 W	η 88 %	196·68·45	011-929221 0
60 W	η 87 %	223·66·55	011-929231 0

SYSTEM SPLITTER

TYPE	ORDER CODE
3 way	011-923830 0
6 way	011-923860 0

Order options

NOTE
Products from the Showcase Lighting range are excluded from returns.

Pole overview





L-SUPPORT standing

EN Arranged linearly along the showcase table, FINA support System, electrically and mechanically connected via the L-Support Poles, ensures excellent illumination of the products or exhibits without restricting the view.

DE Lineare angeordnet entlang des Vitrinen Tisches sorgt FINA support System, elektrisch und mechanisch über die L-Support Pole verbunden, für eine hervorragende Ausleuchtung der Ware oder Exponate, ohne den Blick darauf einzuschränken.





T-SUPPORT standing

EN The T-Support Pole of the FINA support system is primarily used for large display case when several light insets are combined and arranged in a row. The T-Support poles are used to connect them together electrically and mechanically.

DE Die T-Support Pole des FINA support Systems findet vor allem bei großen Vitrinenflächen ihren Einsatz, wenn mehrere Lichteinsätze kombiniert und aneinandergereiht werden. Mittels der T-Support Pole werden diese elektrisch und mechanisch miteinander verbunden.





Y-SUPPORT standing

EN The Y-connectors of the FINA support system enable ideal illumination of the entire display case by allowing different insets to be mechanically and electrically connected to each other, even via corners.

DE Die Y-Connectors des FINA support Systems ermöglichen eine ideale Ausleuchtung der gesamten Vitrine, indem unterschiedliche Insets auch über Ecken miteinander mechanisch und elektrisch verbunden werden können.