

NOBA

suspended


EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; lente de cristal plano-convexa alta calidad; no sombras múltiples; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90 / 2 SDCM (initial MacAdam)
 hasta 158 lm/W
 L80 / 50000 h
 DALI-2, non attenuable
 IP20

Types




Color



Cable



Distribución luminosa



free positioning
by cable and
hook




high quality
glass lens

**NOBA 40 suspended****WIDE FLOOD** 69°, CRI ≥ 90



FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.9 W,	2700 K	726 lm	149 lm/W	0 4 9 - 5 3 1 0 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	664 lm	136 lm/W	0 4 9 - 5 3 1 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	695 lm	143 lm/W	0 4 9 - 5 3 1 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 50 suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.8 W,	2700 K	752 lm	155 lm/W	0 4 9 - 5 3 1 3 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	681 lm	141 lm/W	0 4 9 - 5 3 1 3 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	713 lm	147 lm/W	0 4 9 - 5 3 1 3 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 60 suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.8 W,	2700 K	765 lm	158 lm/W	0 4 9 - 5 3 1 6 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	691 lm	143 lm/W	0 4 9 - 5 3 1 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	723 lm	150 lm/W	0 4 9 - 5 3 1 6 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W


**Mounting accessories (required)****MOUNTING SET** trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	9-25 mm	75-48	0 0 5 - 3 5 1 1 1 1 7

excl. power supply

Order options

COLOUR	COLOUR	COLOUR	CABLE
brushed brass	<input checked="" type="checkbox"/> traffic white RAL 9016	<input checked="" type="checkbox"/> traffic white RAL 9016	<input checked="" type="checkbox"/> white
chrome	4 jet black RAL 9005	8 jet black RAL 9005	8 black
gun metal	5 rose gold	9	
brushed aluminium	6		


**MOUNTING SET with trim for ceilings, 2-25 mm**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	77-49	0 0 5 - 3 5 2 1 1 1 7
jet black	77-49	0 0 5 - 3 5 2 1 1 1 8

excl. power supply

Mounting accessories (optional)**HOOK surface**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	16-30	0 3 0 - 1 0 0 0 0 1 7
jet black	16-30	0 3 0 - 1 0 0 0 0 1 8


Mounting tools accessories (optional)**SPECIAL MOUNTING TOOL for ARY | MOVE IN 45 | NOBA trimless | TULA**

Ø-H (mm)	ORDER CODE
100-107	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless


Electrical accessories (required)**POWER SUPPLY 150 mA, 198-264 V AC, PC2**

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
6 W non DIM	η 80 %	93-36-25	0 0 2 - 9 0 8 1 0
15 W DALI-2	η 87 %	112-29-21	0 0 2 - 9 0 8 1 1

**CANOPY**

CONTROL	Ø-H (mm)	ORDER CODE
non DIM	115-29	0 0 5 - 2 6 0 1 2 1 [i]
DALI-2	115-29	0 0 5 - 2 6 0 1 2 3 [i]

incl. power supply

Electrical accessories (optional)**DIN RAIL POWER SUPPLY BASIC 48 V**

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10-40V

Order options

COLOUR	COLOUR	COLOUR	CABLE
brushed brass 3	<input checked="" type="checkbox"/> traffic white RAL 9016 7	traffic white RAL 9016 7	white 7
chrome 4	jet black RAL 9005 8	jet black RAL 9005 8	black 8
gun metal 5	rose gold 9		
brushed aluminium 6			