



SASSO 100 round

wall


^{EN} Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

^{ES} Aplique de pared cilíndrico de aluminio para el montaje en superficie; inserto lumin. pintado; superf. carcasa con recubr. de polvo; disponible con proyección simétrica directa o proyección directa/indirecta; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; proyección precisa con óptica de lente de alta calidad; variante de montaje DIRECT disponible para la iluminación del suelo o el techo; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI \geq 90 / 2 SDCM (initial MacAdam)
hasta ↓ 1,200 lm / ↑ 1,200 lm
hasta 69 lm/W
L80 / 50000 h
DALI-2, non attenuable
IP20

Types



Color



Color interno



Distribución luminosa



direct and
direct / indirect
illumination



high quality lens



easy mounting



CRI \geq 95 2
SDCM
(optional)




SASSO 100 round direct wall



OPAL LENS | DIRECT 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	0 4 8 - 3 4 5 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	1150 lm	64 lm/W	0 4 8 - 3 4 5 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3500 K	1170 lm	65 lm/W	0 4 8 - 3 4 5 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	1200 lm	67 lm/W	0 4 8 - 3 4 5 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O




SASSO 100 round direct / indirect wall



OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	2700 K	↓1110/↑1110 lm	63 lm/W	0 4 8 - 3 4 6 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	↓1150/↑1150 lm	66 lm/W	0 4 8 - 3 4 6 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 3500 K/ ↑3000 K	↓1170/↑1170 lm	67 lm/W	0 4 8 - 3 4 6 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 4000 K/ ↑4000K	↓1200/↑1200 lm	69 lm/W	0 4 8 - 3 4 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



Optical accessories (optional)



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø-H (mm)	ORDER CODE
jet black	50:3	0 0 7 - 1 9 6 5 5 9 8

Order options

CONTROL	COLOUR	INNER COLOUR
non DIM	1 jet black RAL 9005	1 jet black RAL 9005
DALI-2	3 traffic white RAL 9016	7 matt silver
		4 traffic white RAL 9016
		7 gold dust RAL 260-M
		9

MAM Competence Center, Großhöflein

Austria

Arquitecto

INNOCAD Architektur
ZT

Lighting Design


INNOCAD Architektur
ZT

Fotografía

Paul Ott



Productos utilizados



SASSO 100 round wall



SASSO 100 round suspended



TASK round suspended



SONIC free standing



LITO 60 suspended

