



## SASSO 100 round

wall


<sup>EN</sup> Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

<sup>ES</sup> Aplique de pared cilíndrico de aluminio para el montaje en superficie; inserto lumin. pintado; superf. carcasa con recubr. de polvo; disponible con proyección simétrica directa o proyección directa/indirecta; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; proyección precisa con óptica de lente de alta calidad; variante de montaje DIRECT disponible para la iluminación del suelo o el techo; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
CRI ≥ 90 / 2 SDCM (initial MacAdam)  
hasta ↓ 1,200 lm / ↑ 1,200 lm  
hasta 69 lm/W  
L80 / 50000 h  
DALI-2, non attenuable  
IP20

### Types



### Color



### Color interno



### Distribución luminosa



direct and  
direct / indirect  
illumination



high quality lens



easy mounting



CRI ≥ 95 2  
SDCM  
(optional)




### SASSO 100 round direct wall



#### OPAL LENS | DIRECT 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	0 4 8 - 3 4 5 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	1150 lm	64 lm/W	0 4 8 - 3 4 5 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3500 K	1170 lm	65 lm/W	0 4 8 - 3 4 5 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	1200 lm	67 lm/W	0 4 8 - 3 4 5 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



### SASSO 100 round direct / indirect wall



#### OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	2700 K	↓1110/↑1110 lm	63 lm/W	0 4 8 - 3 4 6 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	↓1150/↑1150 lm	66 lm/W	0 4 8 - 3 4 6 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 3500 K/ ↑3000 K	↓1170/↑1170 lm	67 lm/W	0 4 8 - 3 4 6 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 4000 K/ ↑4000K	↓1200/↑1200 lm	69 lm/W	0 4 8 - 3 4 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



### Optical accessories (optional)



#### HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø-H (mm)	ORDER CODE
jet black	50.3	0 0 7 - 1 9 6 5 5 9 8

### Order options

CONTROL	COLOUR	INNER COLOUR
non DIM	jet black RAL 9005	jet black RAL 9005
DALI-2	traffic white RAL 9016	matt silver
		traffic white RAL 9016
		gold dust RAL 260-M

# MAM Competence Center, Großhöflein

Austria

## Arquitecto

INNOCAD Architektur  
ZT

## Lighting Design

INNOCAD Architektur  
ZT

## Fotografía

Paul Ott



## Productos utilizados



**TASK round  
suspended**



**SONIC free standing**



**SASSO 100 round  
suspended**



**LITO 60 suspended**



**SASSO 100 round  
wall**





