

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 22, UGR ≤ 25
hasta ↓ 1.200 lm / ↑ 1.200 lm
hasta 69 lm/W
L90 / 100000 h
DALI-2, non atenuable
IP20

Types



Colours

Color interno

Distribución luminosa

SASSO 100 round

wall

EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Aplique de pared cilíndrico de aluminio para el montaje en superficie; inserto lumin. pintado; superf. carcasa con recubr. de polvo; disponible con proyección simétrica directa o proyección directa/indirecta; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; proyección precisa con óptica de lente de alta calidad; variante de montaje DIRECT disponible para la iluminación del suelo o el techo; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



direct and direct / indirect illumination



high quality lens



easy mounting



CRI ≥ 95 2 SDCM (optional)





SASSO 100 round direct wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	048 - 345 09 ◆ ◪ ■ O
	3000 K	1150 lm	64 lm/W	048 - 345 00 ◆ ◪ ■ O
	3500 K	1170 lm	65 lm/W	048 - 345 02 ◆ ◪ ■ O
	4000 K	1200 lm	67 lm/W	048 - 345 01 ◆ ◪ ■ O



SASSO 100 round direct / indirect wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	2700 K	↧1110/↥1110 lm	63 lm/W	048 - 346 09 ◆ ◪ ■ O
	3000 K	↧1150/↥1150 lm	66 lm/W	048 - 346 00 ◆ ◪ ■ O
	↧ 3500 K/ ↥3000 K	↧1170/↥1170 lm	67 lm/W	048 - 346 02 ◆ ◪ ■ O
	↧ 4000 K/ ↥4000K	↧1200/↥1200 lm	69 lm/W	048 - 346 01 ◆ ◪ ■ O

Optical accessories



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø·H (mm)	ORDER CODE
jet black	50·3	007 - 196 5598

Order options

CONTROL ◆		COLOUR ◪		INNER COLOUR ■	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9

MAM Competence Center, Großhöflein

Austria

Arquitecto
INNOCAD Architektur
ZT

Lighting Design
INNOCAD Architektur
ZT

Fotografía
Paul Ott



Productos utilizados



TASK round suspended



LITO 60 suspended



SONIC free standing



SASSO 100 round suspended



SASSO 100 round wall

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



