



MITA circle 200

recessed


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; suitable for ceiling thickness of 2-25mm; surface powder coated; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

ES Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; luminaria empotrable con marco; para instalación en techos de 2-25mm de grosor; superficie con recubrimiento de pintura en polvo; reflector de alto brillo con óptica facetada; difusor opal de alta calidad que proporciona una iluminación uniforme; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI \geq 80, CRI \geq 90 / 3 SDCM
(initial MacAdam)
UGR \leq 19
hasta 139 lm/W
L90 / 100000 h, L90 / 50000 h
DALI-2
Opal, Reflector
IP20

Types



Color



Reflector



Distribución luminosa




suitable for
plasterboard or
grid ceilings




DIN EN 12464-1
UGR \leq 19



tunable white
2700 - 6500 K




MITA CIRCLE 200 opal trim




OPAL DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|----------------------|-----------|----------|---|
| 17.2 W | 3000 K, CRI ≥ 90 | 1670 lm | 97 lm/W | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> O |
| | 4000 K, CRI ≥ 90 | 1670 lm | 97 lm/W | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> O |
| 17.5 W | 3000 K, CRI ≥ 80 | 1760 lm | 101 lm/W | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> O |
| | 4000 K, CRI ≥ 80 | 1830 lm | 105 lm/W | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> O |
| 21.6 W | tunable w., CRI ≥ 90 | 1820 lm | 84 lm/W | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> O |




MITA CIRCLE 200 reflector trim



REFLECTOR DALI-2

| SYSTEM | COLOUR TEMP. | REFLECTOR | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|----------------------|-----------|-----------|----------|---|
| 13.2 W | 3000 K, CRI ≥ 90 | chrome | 1700 lm | 129 lm/W | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> R |
| | | dark chr. | 1220 lm | 92 lm/W | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> B |
| | 4000 K, CRI ≥ 90 | chrome | 1700 lm | 129 lm/W | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> R |
| | | dark chr. | 1220 lm | 92 lm/W | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> B |
| 13.5 W | 3000 K, CRI ≥ 80 | chrome | 1800 lm | 133 lm/W | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> R |
| | | dark chr. | 1290 lm | 96 lm/W | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> B |
| | 4000 K, CRI ≥ 80 | chrome | 1870 lm | 139 lm/W | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> R |
| | | dark chr. | 1340 lm | 99 lm/W | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> B |
| 15.6 W | tunable w., CRI ≥ 90 | chrome | 1750 lm | 112 lm/W | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> R |
| | | dark chr. | 1250 lm | 80 lm/W | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> B |



Order options

| COLOUR | |
|------------------------|---------------------------------------|
| traffic white RAL 9016 | 7 <input checked="" type="checkbox"/> |
| jet black RAL 9005 | 8 <input checked="" type="checkbox"/> |