



NOBA

multi suspended



EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; base de techo redonda (blanca o negra) de montaje en superficie para la instalación de dos a cinco o de dos a diez lámparas; o base de techo lineal (blanca o negra) de montaje en superficie para la instalación de dos a cinco lámparas; lente de cristal plano-convexa alta calidad; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 hasta 153 lm/W
 L80 / 50000 h
 IP20


Types



Color



Distribución luminosa



free positioning
 by cable and
 hook




high quality
 glass lens

**NOBA 40 multi suspended****WIDE FLOOD** 69°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	326 lm	133 lm/W	0 4 9 - 5 4 1 0 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	322 lm	135 lm/W	0 4 9 - 5 4 1 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	352 lm	144 lm/W	0 4 9 - 5 4 1 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 50 multi suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	345 lm	141 lm/W	0 4 9 - 5 4 1 3 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	342 lm	143 lm/W	0 4 9 - 5 4 1 3 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	374 lm	153 lm/W	0 4 9 - 5 4 1 3 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 60 multi suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.5 W,	2700 K	325 lm	132 lm/W	0 4 9 - 5 4 1 6 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	337 lm	137 lm/W	0 4 9 - 5 4 1 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	352 lm	143 lm/W	0 4 9 - 5 4 1 6 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W


**Mounting accessories (optional)****HOOK surface**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	16:30	0 3 0 - 1 0 0 0 0 1 7
jet black	16:30	0 3 0 - 1 0 0 0 0 1 8

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>	CABLE	<input checked="" type="checkbox"/>
brushed brass	3	traffic white RAL 9016	7	traffic white RAL 9016	7	white	7
chrome	4	jet black RAL 9005	8	jet black RAL 9005	8	black	8
gun metal	5	rose gold	9				
brushed aluminium	6						


Electrical accessories (required)



CANOPY WITH SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø-H (mm)	ORDER CODE
DALI-2	380-43	0 0 5 - 2 6 9 0 1 3 <input checked="" type="checkbox"/>
Casambi	380-43	0 0 5 - 2 6 9 0 1 9 <input checked="" type="checkbox"/>


2 converter a 300 mA; 2 DALI addresses



CANOPY WITH SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø-H (mm)	ORDER CODE
DALI-2	380-43	0 0 5 - 2 6 9 0 0 3 <input checked="" type="checkbox"/>
Casambi	380-43	0 0 5 - 2 6 9 0 0 9 <input checked="" type="checkbox"/>


1 DALI address



CANOPY WITHOUT SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø-H (mm)	ORDER CODE
DALI-2	380-43	0 0 5 - 2 6 9 1 1 3 <input checked="" type="checkbox"/>
Casambi	380-43	0 0 5 - 2 6 9 1 1 9 <input checked="" type="checkbox"/>


2 converter a 300 mA; 2 DALI addresses



CANOPY WITHOUT SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø-H (mm)	ORDER CODE
DALI-2	380-43	0 0 5 - 2 6 9 1 0 3 <input checked="" type="checkbox"/>
Casambi	380-43	0 0 5 - 2 6 9 1 0 9 <input checked="" type="checkbox"/>

1 DALI address



CANOPY multi linear 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	L-W-H (mm)	ORDER CODE
DALI-2	1000-34-50	0 0 5 - 2 6 9 2 0 3 <input checked="" type="checkbox"/>
Casambi	1000-34-50	0 0 5 - 2 6 9 2 0 9 <input checked="" type="checkbox"/>

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>	CABLE	<input checked="" type="checkbox"/>
brushed brass	3	traffic white RAL 9016	7	traffic white RAL 9016	7	white	7
chrome	4	jet black RAL 9005	8	jet black RAL 9005	8	black	8
gun metal	5	rose gold	9				
brushed aluminium	6						