



## NOBA

multi suspended



<sup>EN</sup> Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

<sup>ES</sup> Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; base de techo redonda (blanca o negra) de montaje en superficie para la instalación de dos a cinco o de dos a diez lámparas; o base de techo lineal (blanca o negra) de montaje en superficie para la instalación de dos a cinco lámparas; lente de cristal plano-convexa alta calidad; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90 / 2 SDCM  
 hasta 153 lm/W  
 L80 / 50000 h  
 IP20

### Types




### Color



### Cable



### Distribución luminosa



free positioning  
by cable and  
hook



high quality  
glass lens




### NOBA 40 multi suspended



**WIDE FLOOD** 69°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	326 lm	133 lm/W	0 4 9 - 5 4 1 0 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	322 lm	135 lm/W	0 4 9 - 5 4 1 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	352 lm	144 lm/W	0 4 9 - 5 4 1 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W




### NOBA 50 multi suspended



**WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	345 lm	141 lm/W	0 4 9 - 5 4 1 3 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	342 lm	143 lm/W	0 4 9 - 5 4 1 3 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	374 lm	153 lm/W	0 4 9 - 5 4 1 3 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W




### NOBA 60 multi suspended



**WIDE FLOOD** 67°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.5 W,	2700 K	325 lm	132 lm/W	0 4 9 - 5 4 1 6 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
9 Vf,	3000 K	337 lm	137 lm/W	0 4 9 - 5 4 1 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
300 mA	4000 K	352 lm	143 lm/W	0 4 9 - 5 4 1 6 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W



#### Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>	CABLE	<input checked="" type="checkbox"/>
brushed brass	3	traffic white RAL 9016	7	white	7
chrome	4	jet black RAL 9005	8	black	8
gun metal	5	rose gold	9		
brushed aluminium	6				


## Electrical mounting accessories (required)



**CANOPY WITH SLOTS multi round 2-5 insets** 220-240 V AC, 50-60 Hz, PC 1, 300 mA

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
DALI-2	traffic white	380-43	0 0 5 - 2 6 9 0 0 3 7
DALI-2	jet black	380-43	0 0 5 - 2 6 9 0 0 3 8
Casambi	traffic white	380-43	0 0 5 - 2 6 9 0 0 9 7
Casambi	jet black	380-43	0 0 5 - 2 6 9 0 0 9 8


1 DALI address



**CANOPY WITH SLOTS multi round 2-10 insets** 220-240 V AC, 50-60 Hz, PC 1, 300 mA

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
DALI-2	traffic white	380-43	0 0 5 - 2 6 9 0 1 3 7
DALI-2	jet black	380-43	0 0 5 - 2 6 9 0 1 3 8
Casambi	traffic white	380-43	0 0 5 - 2 6 9 0 1 9 7
Casambi	jet black	380-43	0 0 5 - 2 6 9 0 1 9 8


2 converter a 300 mA; 2 DALI addresses



**CANOPY WITHOUT SLOTS multi round 2-5 insets** 220-240 V AC, 50-60 Hz, PC 1, 300 mA

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
DALI-2	traffic white	380-43	0 0 5 - 2 6 9 1 0 3 7
DALI-2	jet black	380-43	0 0 5 - 2 6 9 1 0 3 8
Casambi	traffic white	380-43	0 0 5 - 2 6 9 1 0 9 7
Casambi	jet black	380-43	0 0 5 - 2 6 9 1 0 9 8


1 DALI address



**CANOPY WITHOUT SLOTS multi round 2-10 insets** 220-240 V AC, 50-60 Hz, PC 1, 300 mA

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
DALI-2	traffic white	380-43	0 0 5 - 2 6 9 1 1 3 7
DALI-2	jet black	380-43	0 0 5 - 2 6 9 1 1 3 8
Casambi	traffic white	380-43	0 0 5 - 2 6 9 1 1 9 7
Casambi	jet black	380-43	0 0 5 - 2 6 9 1 1 9 8

2 converter a 300 mA; 2 DALI addresses



**CANOPY multi linear 2-5 insets** 220-240 V AC, 50-60 Hz, PC 1, 300 mA

TYPE	COLOUR	L-W-H (mm)	ORDER CODE
DALI-2	traffic white	1000-34-50	0 0 5 - 2 6 9 2 0 3 7
DALI-2	jet black	1000-34-50	0 0 5 - 2 6 9 2 0 3 8
Casambi	traffic white	1000-34-50	0 0 5 - 2 6 9 2 0 9 7
Casambi	jet black	1000-34-50	0 0 5 - 2 6 9 2 0 9 8

## Mounting accessories (optional)



**HOOK surface**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	16-30	0 3 0 - 1 0 0 0 0 1 7
jet black	16-30	0 3 0 - 1 0 0 0 0 1 8