



SASSO 100 round adjustable

recessed 2 lamps


EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; light insets rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie lacada; con marco; con dos luces; elementos de luz girable e inclinable; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K, colour warm dimming 1800 - 3000 K, tunable white 1800 - 4000 K, tunable white 2700 - 6500 K
 CRI \geq 90, CRI \geq 92 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
 UGR \leq 10, UGR \leq 13, UGR \leq 16, UGR \leq 19
 hasta 127 lm/W
 L80 / 50000 h, L85 / 50000 h, L90 / 50000 h
 DALI-2, non attenuable
 front IP40, back IP20

Types



Color



Set de montaje



Distribución luminosa



360° rotatable,
30° tiltable



glare control
(UGR \leq 16)



Colour Warm
Dimming 1800 -
3000 K



CRI \geq 95 2
SDCM
(optional)



SASSO 100 round adjustable (tunable white)



MEDIUM 33°, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.1 W	2700 - 6500 K (tunable w., CRI ≥ 92)	1800 lm	75 lm/W	0 4 8 - 2 7 2 0 D 3 <input checked="" type="checkbox"/> M
27.6 W	1800 - 4000 K (tunable w., CRI ≥ 90)	1980 lm	72 lm/W	0 4 8 - 2 7 2 0 L 3 <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour traffic white, matt silver. DALI-2 power supply included

WIDE FLOOD 53°, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.1 W	2700 - 6500 K (tunable w., CRI ≥ 92)	1860 lm	77 lm/W	0 4 8 - 2 7 2 0 D 3 <input checked="" type="checkbox"/> W
27.6 W	1800 - 4000 K (tunable w., CRI ≥ 90)	2040 lm	74 lm/W	0 4 8 - 2 7 2 0 L 3 <input checked="" type="checkbox"/> W

DALI-2 power supply included



SASSO 100 round adjustable



SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1740 lm	115 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> S
	3000 K	2x1800 lm	118 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> S
	3500 K	2x1840 lm	121 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> S
	4000 K	2x1880 lm	123 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> S
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2400 lm	106 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> S
	3000 K	2x2430 lm	107 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> S
	3500 K	2x2490 lm	110 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> S
	4000 K	2x2550 lm	112 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> S

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

MEDIUM 31°-34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1750 lm	115 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> M
	3000 K	2x1800 lm	118 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> M
	3500 K	2x1840 lm	121 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> M
	4000 K	2x1890 lm	124 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> M
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2410 lm	106 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> M
	3000 K	2x2440 lm	108 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> M
	3500 K	2x2500 lm	110 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> M
	4000 K	2x2560 lm	113 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> M
2x23.8 W, 700 mA	CWD	2x2060 lm	87 lm/W	0 4 8 - 2 7 2 0 E 1 <input checked="" type="checkbox"/> M

The data values for the luminaire luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour traffic white, matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

FLOOD 39°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1660 lm	109 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> F
	3000 K	2x1710 lm	113 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> F
	3500 K	2x1750 lm	115 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> F
	4000 K	2x1790 lm	118 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> F
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2290 lm	101 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> F
	3000 K	2x2320 lm	102 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> F
	3500 K	2x2380 lm	105 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> F
	4000 K	2x2430 lm	107 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> F

The data values for the luminaire luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour traffic white.

WIDE FLOOD 51°-56°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1800 lm	118 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> W
	3000 K	2x1850 lm	121 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> W
	3500 K	2x1890 lm	124 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> W
	4000 K	2x1940 lm	127 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> W
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2470 lm	109 lm/W	0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> W
	3000 K	2x2500 lm	110 lm/W	0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> W
	3500 K	2x2560 lm	113 lm/W	0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> W
	4000 K	2x2620 lm	116 lm/W	0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> W
2x23.8 W, 700 mA	CWD	2x2290 lm	96 lm/W	0 4 8 - 2 7 2 0 E 1 <input checked="" type="checkbox"/> W

CWD only for DALI-2; not for DIN-RAIL LED Driver

Electrical mounting accessories (optional)**THROUGH WIRING CONNECTION BOX**

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)**MOUNTING SET with trim 2 lamps** for intermediate ceilings, 2-25 mm

L-W-H (mm)	ORDER CODE
218-118-35	0 4 8 - 2 7 9 8 3 1 <input checked="" type="checkbox"/>


Electrical accessories (required)**POWER SUPPLY PC2**

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA 21 W non DIM	198-264 V AC	η 86 %	143-43-30	0 0 2 - 9 0 7 6 6
450 mA 28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 6 7
700 mA 28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 7 6
650 mA 31 W non DIM	198-264 V AC	η 88 %	143-43-30	0 0 2 - 9 0 7 8 0
650 mA 28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 8 9

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 6 7 A
650 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 8 9 A
700 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 7 6 A
450 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 6 6 A
650 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 8 0 A
700 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 7 4 A

Optical accessories (optional)



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø-H (mm)	ORDER CODE
jet black	50-3	0 0 7 - 1 9 6 5 5 9 8

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		