




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K, colour warm dimming 1800 - 3000 K, tunable white 1800 - 4000 K, tunable white 2700 - 6500 K
CRI ≥ 90, CRI ≥ 92 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16, UGR ≤ 19
hasta 127 lm/W
L85 / 50000 h, L90 / 100000 h
DALI-2, non atenuable
front IP40, back IP20

Types




Colours



Set de montaje



Distribución luminosa



SASSO 100 square adjustable

recessed 1 lamp

EN Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; light inset tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable cuadrado; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; elemento de luz inclinable; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática


glare control (UGR ≤ 16)


60 mm recessed depth


Colour Warm Dimming 1800 – 3000 K


CRI ≥ 95 2 SDCM (optional)




SASSO 100 square adjustable (tunable white)

30° | TUNABLE WHITE | CRI ≥92 | UGR ≤19 | 220-240 V | 1 ADDR. | IP20 IP40 | X-PERT | X-PERT

MEDIUM 33°, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
21.0 W	tunable w.	1670 lm	80 lm/W	0 4 8 - 2 7 3 0 ◪ 3 ◪ M

The data values for the luminous flux of fraction may differ for specific order options by -7%. Luminous flux value refers to colour traffic white, matt silver colour temperature range 2700 - 6500 K. DALI-2 power supply included



WIDE FLOOD 53°, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
21.0 W	tunable w.	1720 lm	82 lm/W	0 4 8 - 2 7 3 0 ◪ 3 ◪ W

DALI-2 power supply included



SASSO 100 square adjustable

30° | CRI ≥90 | 2 SDCM | UGR ≤10 | cd/m² ≤1500 | III | 1 ADDR. | IP20 IP40 | X-PERT

SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.2 W, 36 Vf, 450 mA	2700 K	1750 lm	115 lm/W	0 4 8 - 2 7 3 0 9 1 ◪ S
	3000 K	1800 lm	118 lm/W	0 4 8 - 2 7 3 0 0 1 ◪ S
	3500 K	1840 lm	121 lm/W	0 4 8 - 2 7 3 0 2 1 ◪ S
	4000 K	1880 lm	124 lm/W	0 4 8 - 2 7 3 0 1 1 ◪ S
22.7 W, 36 Vf, 650 mA	2700 K	2400 lm	106 lm/W	0 4 8 - 2 7 3 0 9 1 ◪ S
	3000 K	2440 lm	107 lm/W	0 4 8 - 2 7 3 0 0 1 ◪ S
	3500 K	2490 lm	110 lm/W	0 4 8 - 2 7 3 0 2 1 ◪ S
	4000 K	2550 lm	112 lm/W	0 4 8 - 2 7 3 0 1 1 ◪ S

The data values for the luminous flux of fraction may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

MEDIUM 31°-34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.2 W, 36 Vf, 450 mA	2700 K	1750 lm	115 lm/W	0 4 8 - 2 7 3 0 9 1 ◪ M
	3000 K	1810 lm	119 lm/W	0 4 8 - 2 7 3 0 0 1 ◪ M
	3500 K	1850 lm	121 lm/W	0 4 8 - 2 7 3 0 2 1 ◪ M
	4000 K	1890 lm	124 lm/W	0 4 8 - 2 7 3 0 1 1 ◪ M
22.7 W, 36 Vf, 650 mA	2700 K	2410 lm	106 lm/W	0 4 8 - 2 7 3 0 9 1 ◪ M
	3000 K	2450 lm	108 lm/W	0 4 8 - 2 7 3 0 0 1 ◪ M
	3500 K	2500 lm	110 lm/W	0 4 8 - 2 7 3 0 2 1 ◪ M
	4000 K	2560 lm	113 lm/W	0 4 8 - 2 7 3 0 1 1 ◪ M
23.8 W, 700 mA	CWD	2070 lm	87 lm/W	0 4 8 - 2 7 3 0 E 1 ◪ M

The data values for the luminous flux of fraction may differ for specific order options by -6%. Luminous flux value refers to colour traffic white, matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

Order options

COLOUR TEMPERATURE RANGE ◪	
2700 - 6500 K	D
1800 - 4000 K	L

COLOUR ◪	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

FLOOD 39°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.2 W, 36 Vf, 450 mA	2700 K	1670 lm	110 lm/W	048-273091F
	3000 K	1720 lm	113 lm/W	048-273001F
	3500 K	1760 lm	116 lm/W	048-273021F
	4000 K	1800 lm	118 lm/W	048-273011F
22.7 W, 36 Vf, 650 mA	2700 K	2300 lm	101 lm/W	048-273091F
	3000 K	2330 lm	103 lm/W	048-273001F
	3500 K	2390 lm	105 lm/W	048-273021F
	4000 K	2440 lm	107 lm/W	048-273011F


The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to colour traffic white.

WIDE FLOOD 51°-56°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.2 W, 36 Vf, 450 mA	2700 K	1800 lm	118 lm/W	048-273091W
	3000 K	1850 lm	121 lm/W	048-273001W
	3500 K	1890 lm	124 lm/W	048-273021W
	4000 K	1940 lm	127 lm/W	048-273011W
22.7 W, 36 Vf, 650 mA	2700 K	2470 lm	109 lm/W	048-273091W
	3000 K	2500 lm	110 lm/W	048-273001W
	3500 K	2560 lm	113 lm/W	048-273021W
	4000 K	2620 lm	116 lm/W	048-273011W
23.8 W, 700 mA	CWD	2300 lm	97 lm/W	048-27330E1W

CWD only for DALI-2; not for DIN-RAIL LED Driver

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 0
DALI cable ø 4 – 12 mm	105·58·30	005-255111 0


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	105·105·29	048-279711 7




MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
traffic white	118·118·35	048-279731 7
jet black	118·118·35	048-279731 8
white aluminium	118·118·35	048-279731 G

Order options

COLOUR		COLOUR	
jet black RAL 9005	1	white aluminium RAL 9006	
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-269511 0

order mounting set separately


Electrical accessories (required)

POWER SUPPLY PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA | 21 W | non DIM	198-264 V AC	η 86 %	143·43·30	002-907666
450 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-907677
700 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-907776
650 mA | 28 W | non DIM	198-264 V AC	η 88 %	143·43·30	002-907800
650 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-907899

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA | DALI-2	176-264 V AC	η 85 %	002-907677A
650 mA | DALI-2	176-264 V AC	η 85 %	002-907899A
700 mA | DALI-2	176-264 V AC	η 85 %	002-907776A
450 mA | non DIM	198-264 V AC	η 88 %	002-907666A
650 mA | non DIM	198-264 V AC	η 88 %	002-907800A
700 mA | non DIM	198-264 V AC	η 88 %	002-907744A

2 power supplies for 2 lamps variants necessary