



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
hasta 119 lm/W
L80 / 75000 h
DALI-2, non atenuable
front IP20

Types

trim



trimless



Colours

Set de montaje

Distribución luminosa

SASSO 40 round wallwasher/floor

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminium-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogeneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática




wallwasher/ wallwasher floor inset



60 mm recess depth (DIN rail)



SASSO 40 round wallwasher/floor






WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W, 36 Vf, 200 mA	2700 K	829 lm	119 lm/W	048-284091 W
	3000 K	780 lm	112 lm/W	048-284001 W
	3500 K	812 lm	117 lm/W	048-284021 W
	4000 K	829 lm	119 lm/W	048-284011 W


The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

Mounting accessories (required)




MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	56·29	048-2896117




MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	64·25	048-2896197



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic


COLOUR	Ø·H (mm)	ORDER CODE
traffic white	64·27	048-2896397
jet black	64·27	048-2896398



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	60·40	048-2896317
jet black	60·40	048-2896318

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings

COLOUR	ORDER CODE
traffic black	048-2895918

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
traffic black	RAL 9017


Electrical accessories (required)

POWER SUPPLY 200 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
15 W | DALI-2	η 87 %	165·29·21	002-90740
10 W | non DIM	η 80 %	65·39·20	002-90744

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-6520210

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-6121030

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
450 mA	η 87 %	002-90750A
200 mA	η 87 %	002-90749A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA	η 87 %	185·30·21	002-90750
200 mA	η 87 %		002-90749

2 power supplies for 2 lamps variants necessary