



## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
hasta 118 lm/W
L80 / 75000 h
DALI-2, non atenuable
front IP20

### Types




### Colours

### Set de montaje

### Distribución luminosa

# **SASSO 40** round wallwasher/floor

recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie lacada; con marco; con dos luces; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogeneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



wallwasher/
wallwasher floor
inset



## **SASSO 40** round wallwasher/floor





### WALLWASHER FLOOR CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 6.9 W, | 2700 K | 1640 lm | 118 lm/W | 048-284091 W |
| 36 Vf, | 3000 K | 1540 lm | 111 lm/W | 048-284001 W |
| 200 mA | 3500 K | 1610 lm | 116 lm/W | 048-284021 W |
| | 4000 K | 1540 lm | 111 lm/W | 048-284011 W |

2 insets necessary, order code only applies to 1 inset




## Mounting accessories (required)




### MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

| L·W·H (mm) | ORDER CODE |
|---|---|
| 122·60·13 | 048-289831 [1] |


## Electrical accessories (required)

### POWER SUPPLY 200 mA, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 15 W \| DALI-2 | η 87 % | 165·29·21 | 002-90740 |
| 10 W \| non DIM | η 80 % | 65·39·20 | 002-90744 |

2 power supplies for 2 lamps variants necessary

## Electrical accessories (optional)




### DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|---|
| 160 W \| PC2 | 220-240 V AC | η 94 % | 72·90·63 | 005-652021 0 |

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

### DIN RAIL LED DRIVER

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| DALI-2 DT6 1-2 addresses / DT8 1 adress | 36·88·59 | 005-612103 0 |

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

### POWER SUPPLY PRE-WIRED with junction box DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|---|---|---|
| 450 mA | η 87 % | 002-90750 A |
| 200 mA | η 87 % | 002-90749 A |

2 power supplies for 2 lamps variants necessary

**Order options**

| COLOUR | |
|---|---|
| jet black RAL 9005 | 1 |
| matt silver | 4 |
| traffic white RAL 9016 | 7 |
| gold dust RAL 260-M | 9 |

| COLOUR [1] | |
|---|---|
| traffic white RAL 9016 | 7 |
| jet black RAL 9005 | 8 |

**POWER SUPPLY with loop through function** DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 450 mA | η 87 % | 185·30·21 | 0 0 2 - 9 0 7 5 0 |
| 200 mA | η 87 % | | 0 0 2 - 9 0 7 4 9 |

2 power supplies for 2 lamps variants necessary