



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
hasta 109 lm/W
L80 / 75000 h
DALI-2, non atenuable
front IP20

Types



Colours

Set de montaje

Distribución luminosa

SASSO 40 round wallwasher

recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie lacada; con marco; con dos luces; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogeneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



wallwasher/
wallwasher floor inset



SASSO 40 round wallwasher




WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W,	2700 K	1520 lm	109 lm/W	048-284091 A
36 Vf,	3000 K	1430 lm	103 lm/W	048-284001 A
200 mA	3500 K	1490 lm	107 lm/W	048-284021 A
	4000 K	1430 lm	103 lm/W	048-284011 A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver. 2 insets necessary, order code only applies to 1 inset



Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L·W·H (mm)	ORDER CODE
122·60·13	048-289831 1


Electrical accessories (required)

POWER SUPPLY 200 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
15 W | DALI-2	η 87 %	165·29·21	002-90740
10 W | non DIM	η 80 %	65·39·20	002-90744

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
450 mA	η 87 %	002-90750 A
200 mA	η 87 %	002-90749 A

2 power supplies for 2 lamps variants necessary

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 5 0
200 mA	η 87 %		0 0 2 - 9 0 7 4 9

2 power supplies for 2 lamps variants necessary