



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
hasta 118 lm/W
L80 / 75000 h
DALI-2, non atenuable
front IP20

Types



Colours

Set de montaje

Distribución luminosa

SASSO 60 round wallwasher/floor

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminium-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogeneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática



wallwasher/
wallwasher floor
inset



60 mm
recessed depth
(non DIM)



quick mounting
in
soft acoustic
ceilings




SASSO 60 round wallwasher/floor



WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W, 36 Vf, 250 mA	2700 K	1050 lm	118 lm/W	048-264191◪W
	3000 K	985 lm	111 lm/W	048-264101◪W
	3500 K	1030 lm	116 lm/W	048-264121◪W
	4000 K	985 lm	111 lm/W	048-264111◪W

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 0
DALI cable ø 4 – 12 mm	105·58·30	005-255111 0


Linect®-Ready

Mounting accessories (required)

MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/20/25 mm	73·29	048-2696117

for SASSO 60 round | SPIO 60 downlight




MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	80·25	048-2696197



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·27	048-2696397
jet black	80·27	048-2696398



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·40	048-2696317
jet black	80·40	048-2696318
white aluminium	80·40	048-269631G

Order options

COLOUR	◪
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9


COLOUR	
white aluminium	RAL 9006
traffic black	RAL 9017

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	048-269521 0



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-269511 0

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings

COLOUR	L·W·H (mm)	ORDER CODE
traffic black	77·77·35	048-269591 8


Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
10 W | non DIM	η 80 %	65·39·20	002-90742
15 W | DALI-2	η 87 %	165·29·21	002-90748

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	002-90790A
250 mA | 15 W | DALI-2	η 87 %	002-90748A
300 mA | 15 W | non DIM	η 84 %	002-90771A
250 mA | 10 W | non DIM	η 80 %	002-90742A

2 power supplies for 2 lamps variants necessary

Order options

COLOUR	
white aluminium	RAL 9006
traffic black	RAL 9017

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 4 7

2 power supplies for 2 lamps variants necessary