



## SASSO 60 square wallwasher

recessed 1 lamp


**EN** Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

**ES** Proyector empotrable cuadrado; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogéneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI ≥ 90 / 2 SDCM (initial MacAdam)  
 hasta 117 lm/W  
 L85 / 50000 h  
 DALI-2, non attenuable  
 front IP20

### Types



### Color



### Set de montaje



### Distribución luminosa



wallwasher/  
wallwasher floor  
inset



60 mm  
recessed depth



CRI ≥ 95 2  
SDCM  
(optional)




## SASSO 60 square wallwasher




### WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W,	2700 K	1030 lm	117 lm/W	0 4 8 - 2 6 5 1 9 1 <input checked="" type="checkbox"/> A
36 Vf,	3000 K	972 lm	110 lm/W	0 4 8 - 2 6 5 1 0 1 <input checked="" type="checkbox"/> A
250 mA	3500 K	1010 lm	114 lm/W	0 4 8 - 2 6 5 1 2 1 <input checked="" type="checkbox"/> A
	4000 K	972 lm	110 lm/W	0 4 8 - 2 6 5 1 1 1 <input checked="" type="checkbox"/> A



The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.

## Electrical mounting accessories (optional)




### THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

## Mounting accessories (required)



### MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	L-W-H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	72-72-29	0 4 8 - 2 6 9 7 1 1 7



### MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	80-80-21	0 4 8 - 2 6 9 7 3 1 7
jet black	80-80-21	0 4 8 - 2 6 9 7 3 1 8
white aluminium	80-80-21	0 4 8 - 2 6 9 7 3 1 G

## Mounting accessories (optional)



### PRIMED CONCRETE MOUNTING HOUSING

L-W-H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0

order mounting set separately

## Order options


COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		

### Electrical accessories (required)

#### POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
10 W   non DIM	$\eta$ 80 %	65-39-20	0 0 2 - 9 0 7 4 2
15 W   DALI-2	$\eta$ 87 %	165-29-21	0 0 2 - 9 0 7 4 8

### Electrical accessories (optional)



#### DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	$\eta$ 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

#### DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

#### POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 9 0 A
250 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 4 8 A
300 mA   15 W   non DIM	$\eta$ 84 %	0 0 2 - 9 0 7 7 1 A
250 mA   10 W   non DIM	$\eta$ 80 %	0 0 2 - 9 0 7 4 2 A

#### POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 4 7

### Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		