



SASSO 60 square wallwasher

recessed 2 lamps

EN Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable cuadrado; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie lacada; con marco; con dos luces; característica de proyección asimétrica; con reflector asimétrico diseñado para proporcionar un efecto homogéneo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 hasta 117 lm/W
 L85 / 50000 h
 DALI-2, non attenuable
 front IP20

Types

double trim



Color



Set de montaje



Distribución luminosa



wallwasher/
wallwasher floor
inset



60 mm
recessed depth



CRI ≥ 95 2
SDCM
(optional)



SASSO 60 square wallwasher




WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x8.9 W,	2700 K	2x1030 lm	117 lm/W	0 4 8 - 2 6 5 1 9 1 <input checked="" type="checkbox"/> A
36 Vf,	3000 K	2x972 lm	110 lm/W	0 4 8 - 2 6 5 1 0 1 <input checked="" type="checkbox"/> A
250 mA	3500 K	2x1010 lm	114 lm/W	0 4 8 - 2 6 5 1 2 1 <input checked="" type="checkbox"/> A
	4000 K	2x972 lm	110 lm/W	0 4 8 - 2 6 5 1 1 1 <input checked="" type="checkbox"/> A

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm


L-W-H (mm)	ORDER CODE
147-81-35	0 4 8 - 2 6 9 9 3 1 <input checked="" type="checkbox"/>

Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
10 W non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 8

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 -1050 mA settable const. current | 2x42W | 48V DC | U OUT 10-40V

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 4 7

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		