



## MINO 25

suspended


**EN** Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 25 x 25 mm); no visible screws; surface raw or powder coated; pendant fitting with height-adjustable cable suspension; incl. flat cable for power supply; high quality reflector with micro-faceted, aluminum-vaporised surface; or fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; precise radiation characteristic with symmetrical light distribution; or completely homogeneously illuminated, opal cover; converter integrated into luminaire housing; energy-efficient LEDs with very good colour rendering; canopy for through wiring

**ES** Cuerpo de perfil de aluminio con diseño angular; forma extremadamente esbelta (solo 25 x 25 mm); sin tornillos visibles; superficie sin tratar o recubierta por pulverización; colgada mediante suspensión por cable de altura regulable; cable de alimentación plano incluido; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; o equipado con puntos de luz LED individuales; buen control del deslumbramiento mediante plano de punto de luz retranqueado; se ha incrementado la eficiencia debido al uso de la última tecnología en el diseño de lentes; lentes aplicadas con característica de proyección wide flood; precisa característica de emisión con distribución de luz simétrica; o difusor opal de iluminación absolutamente homogénea; convertidor integrado en el cuerpo luminoso; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80 / 3 SDCM (initial MacAdam)  
 UGR ≤ 16, UGR ≤ 19  
 hasta 168 lm/W  
 L90 / 50000 h  
 DALI-2  
 Wideflood  
 IP20

### Types



### Color



### Inserto




### Distribución luminosa




black & chrome  
louver




up to 168 lm/W  
(high efficiency)



super slim  
design




### MINO 25 opal suspended




#### OPAL DALI-2


SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
9.5 W	1004 mm	80	1220 lm	128 lm/W	0 4 3 - 0 2 2 1 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O
		90	1000 lm	105 lm/W	0 4 3 - 0 2 2 1 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O
18.3 W	2004 mm	80	2450 lm	134 lm/W	0 4 3 - 0 2 2 2 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O
		90	2000 lm	109 lm/W	0 4 3 - 0 2 2 2 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O
25.2 W	2754 mm	80	3370 lm	134 lm/W	0 4 3 - 0 2 2 3 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O
		90	2760 lm	110 lm/W	0 4 3 - 0 2 2 3 :: <input checked="" type="checkbox"/> <input type="checkbox"/> O



The data values for the luminous flux may differ for specific order options by -12%. Luminous flux value refers to colour temperature 4000 K.




### MINO 25 louver suspended




#### LOUVER DALI-2


SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1730 lm	162 lm/W	0 4 3 - 0 2 0 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
		90	1420 lm	133 lm/W	0 4 3 - 0 2 0 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
20.6 W	2004 mm	80	3470 lm	168 lm/W	0 4 3 - 0 2 0 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
		90	2840 lm	138 lm/W	0 4 3 - 0 2 0 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
27.5 W	2754 mm	80	4630 lm	168 lm/W	0 4 3 - 0 2 0 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
		90	3790 lm	138 lm/W	0 4 3 - 0 2 0 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>



The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.




### MINO 25 spotline suspended



#### SPOTLINE DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1710 lm	160 lm/W	0 4 3 - 0 2 1 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W
		90	1400 lm	131 lm/W	0 4 3 - 0 2 1 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W
20.6 W	2004 mm	80	3410 lm	166 lm/W	0 4 3 - 0 2 1 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W
		90	2790 lm	135 lm/W	0 4 3 - 0 2 1 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W
27.5 W	2754 mm	80	4560 lm	166 lm/W	0 4 3 - 0 2 1 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W
		90	3730 lm	136 lm/W	0 4 3 - 0 2 1 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W



The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inset traffic white colour temperature 4000 K.

#### Order options

COLOUR TEMPERATURE	COLOUR TEMPERATURE	COLOURS	INSET
3000 K	3000 K	aluminium raw / Cable white	chrome reflector
4000 K	4000 K	aluminium raw / Cable black	black reflector
		signal white / Cable white	
		signal black / Cable black	

INSET	COLOUR
traffic white RAL 9016	signal white RAL 9003
jet black RAL 9005	signal black RAL 9004