

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
L90 / 50000 h
DALI-2, non atenuable
front IP20

Types



Colours



Set de montaje



Distribución luminosa






UNICO Q9

recessed

EN Square recessed multi-downlight made of die-cast aluminium; equipped with nine individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

ES Luz múltiple empotrable descendente cuadrada para montar, de aluminio de colada a presión; equipada con nueve sistemas de lentes elegibles individualmente o de definición fija, específicos para la aplicación; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; montaje eléctrico sencillo con conexión enchufable protegida contra la polarización inversa; apropiada para espesores de techo de 2-25 mm; superficie con recubrimiento de pintura en polvo; posibilidad de instalar distintas carcasas; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; proyección precisa con varias distribuciones de la luz distintas simétricas; o con distribución de luz asimétrica; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



black & chrome reflector



one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)







UNICO Q9



MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ B 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ B 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ B 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ B 0 ◪ 4 1

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ C 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ C 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ C 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ C 0 ◪ 4 1

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ D 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ D 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ D 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ D 0 ◪ 4 1

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ K 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ K 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ K 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ K 0 ◪ 4 1

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ E 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ E 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ E 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ E 0 ◪ 4 1

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ F 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ F 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ F 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ F 0 ◪ 4 1

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090-7Q99 ⇕ G0 ◪ 41
	3000 K	lm	090-7Q90 ⇕ G0 ◪ 41
	3500 K	lm	090-7Q92 ⇕ G0 ◪ 41
	4000 K	lm	090-7Q91 ⇕ G0 ◪ 41


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	2660 lm	090-7Q99 ⇕ A0041
	3000 K	2660 lm	090-7Q90 ⇕ A0041
	3500 K	2770 lm	090-7Q92 ⇕ A0041
	4000 K	2830 lm	090-7Q91 ⇕ A0041

WALLWASHER FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	3130 lm	090-7Q99 ⇕ W0 ◪ 41
	3000 K	3130 lm	090-7Q90 ⇕ W0 ◪ 41
	3500 K	3260 lm	090-7Q92 ⇕ W0 ◪ 41
	4000 K	3330 lm	090-7Q91 ⇕ W0 ◪ 41

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 10
DALI cable ø 4 – 12 mm	105·58·30	005-255111 10

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	122·122·47	090-7Q90 100

for UNICO Q9



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	138·138·30	090-7Q90 20B
traffic white	138·138·30	090-7Q90 20W

for UNICO Q9

Order options


CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

Mounting tools accessories (optional)

DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	0 9 0 - 0 0 2 1 0 0

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator	see POWER SUPPLY PRE-WIRED

Aertssen Group, Beveren

Bélgica

Arquitecto
Mertens Architecten

Lighting Design
Eef Debeuf

Fotografía
Kris Dekeijser



Productos utilizados



MINO 60 CIRCLE suspended



MOVE IT 25 surface / suspended system



SPOTLINE MOVE IT 25




JUST 45 MOVE IT 25 / 25 S / 45



UNICO Q9 recessed



UNICO L2 / L3 recessed



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



















