

## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
hasta 143 lm/W
L90 / 50000 h
DALI-2, non atenuable
front IP20

### Types




### Colours



### Set de montaje



### Distribución luminosa



# UNICO Q9

recessed

EN Square recessed multi-downlight made of die-cast aluminium; equipped with nine individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

ES Luz múltiple empotrable descendente cuadrada para montar, de aluminio de colada a presión; equipada con nueve sistemas de lentes elegibles individualmente o de definición fija, específicos para la aplicación; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; montaje eléctrico sencillo con conexión enchufable protegida contra la polarización inversa; apropiada para espesores de techo de 2-25 mm; superficie con recubrimiento de pintura en polvo; posibilidad de instalar distintas carcasas; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; proyección precisa con varias distribuciones de la luz distintas simétricas; o con distribución de luz asimétrica; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



black & chrome reflector



one luminaire multiple scenes



up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)









## UNICO Q9




### MEDIUM ROUND CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ◆ B0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ◆ B0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ◆ B0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ◆ B0 ◪ 41 |

### FLOOD ROUND CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ◆ C0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ◆ C0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ◆ C0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ◆ C0 ◪ 41 |

### WIDE FLOOD ROUND CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ◆ D0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ◆ D0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ◆ D0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ◆ D0 ◪ 41 |

### SPOT ROUND CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ◆ K0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ◆ K0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ◆ K0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ◆ K0 ◪ 41 |

### MEDIUM SQUARE CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ◆ E0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ◆ E0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ◆ E0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ◆ E0 ◪ 41 |

### Order options

| CONTROL ◆ | | COLOUR ◪ | |
|---|---|---|---|
| non DIM | 1 | chrome reflector | 0 |
| DALI-2 | 3 | black reflector | B |

**FLOOD SQUARE** CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ⇕ F0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ⇕ F0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ⇕ F0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ⇕ F0 ◪ 41 |

**WIDE FLOOD SQUARE** CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | lm | 090-7Q99 ⇕ G0 ◪ 41 |
| | 3000 K | lm | 090-7Q90 ⇕ G0 ◪ 41 |
| | 3500 K | lm | 090-7Q92 ⇕ G0 ◪ 41 |
| | 4000 K | lm | 090-7Q91 ⇕ G0 ◪ 41 |

**WALLWASHER** chrome reflector, CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | 2660 lm | 090-7Q99 ⇕ A0041 |
| | 3000 K | 2660 lm | 090-7Q90 ⇕ A0041 |
| | 3500 K | 2770 lm | 090-7Q92 ⇕ A0041 |
| | 4000 K | 2830 lm | 090-7Q91 ⇕ A0041 |

**WALLWASHER FLOOR** CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 25.7 W | 2700 K | 3130 lm | 090-7Q99 ⇕ W0 ◪ 41 |
| | 3000 K | 3130 lm | 090-7Q90 ⇕ W0 ◪ 41 |
| | 3500 K | 3260 lm | 090-7Q92 ⇕ W0 ◪ 41 |
| | 4000 K | 3330 lm | 090-7Q91 ⇕ W0 ◪ 41 |

## Electrical mounting accessories (optional)




**THROUGH WIRING CONNECTION BOX**

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| non DIM cable ø 4 – 12 mm | 105·58·30 | 005-253111 10 |
| DALI cable ø 4 – 12 mm | 105·58·30 | 005-255111 10 |

Linect®-Ready

## Mounting accessories (required)




**MOUNTING SET trimless** for plasterboard ceilings

| PLASTERBOARD CEILING THICKNESS | L·W·H (mm) | ORDER CODE |
|---|---|---|
| 12.5/15/20/25 mm | 122·122·47 | 090-7Q90 100 |

for UNICO Q9

**Order options**

| CONTROL | ⇕ | COLOUR | ◪ | COLOUR | |
|---|---|---|---|---|---|
| non DIM | 1 | chrome reflector | 0 | jet black | RAL 9005 |
| DALI-2 | 3 | black reflector | B | traffic white | RAL 9016 |




**MOUNTING SET with trim** for intermediate ceilings, 2-25 mm

| COLOUR | L·W·H (mm) | ORDER CODE |
|---|---|---|
| jet black | 138·138·30 | 090-7Q9020B |
| traffic white | 138·138·30 | 090-7Q9020W |

for UNICO Q9

## Mounting tools accessories (optional)

**DISMOUNTING TOOL**

| L·W·H (mm) | ORDER CODE |
|---|---|
| 70·30·2 | 090-002100 |

## Electrical accessories (optional)




**POWER SUPPLY pre-wired**

Available in the configurator — see POWER SUPPLY PRE-WIRED

**Order options**

**COLOUR**

| | |
|---|---|
| jet black | RAL 9005 |
| traffic white | RAL 9016 |

# Aertssen Group, Beveren

Bélgica

**Arquitecto**
Mertens Architecten

**Lighting Design**
Eef Debeuf

**Fotografía**
Kris Dekeijser



**Productos utilizados**



**MINO 60 CIRCLE suspended**



**MOVE IT 25 surface / suspended system**



**SPOTLINE MOVE IT 25**



**JUST 45 MOVE IT 25 / 25 S / 45**



**UNICO Q9 recessed**



**UNICO L2 / L3 recessed**



**SASSO 60 round downlight recessed 1 lamp**

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



















