



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 UGR ≤ 10, UGR ≤ 16, UGR ≤ 19
 hasta 139 lm/W
 L85 / 50000 h
 DALI-2, non attenuable
 IP20

Types



Color



Reflector



Distribución luminosa



UNICO Q1 / Q4


ceiling

^{EN} Square surface mounted multi-downlight made of aluminium; equipped with one (Q1) / four (Q4) individually selectable or pre-specified, customised light element(s); luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering


^{ES} Downlight múltiple de aluminio cuadrada de superficie; equipada con uno (Q1) / cuatro (Q4) sistemas de lentes elegibles individualmente o de definición fija, específicos para la aplicación; cuerpo luminoso insertable en la placa de montaje por enclavamiento y sin necesidad de herramienta; convertidor integrado en el cuerpo luminoso; superficie con recubrimiento de pintura en polvo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; proyección precisa con varias distribuciones de la luz distintas simétricas; o con distribución de luz asimétrica; LEDs de alta eficiencia que proporcionan una alta reproducción cromática



black & chrome reflector



one luminaire multiple scenes




UNICO Q1 ceiling



SPOT ROUND 19°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	396 lm	94 lm/W	0 9 0 - 1 Q 1 9 1 K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	396 lm	94 lm/W	0 9 0 - 1 Q 1 0 1 K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	412 lm	98 lm/W	0 9 0 - 1 Q 1 2 1 K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	420 lm	100 lm/W	0 9 0 - 1 Q 1 1 1 K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1



MEDIUM ROUND 34°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	427 lm	102 lm/W	0 9 0 - 1 Q 1 9 1 B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	427 lm	102 lm/W	0 9 0 - 1 Q 1 0 1 B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	445 lm	106 lm/W	0 9 0 - 1 Q 1 2 1 B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	454 lm	108 lm/W	0 9 0 - 1 Q 1 1 1 B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

FLOOD ROUND 47°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	457 lm	109 lm/W	0 9 0 - 1 Q 1 9 1 C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	457 lm	109 lm/W	0 9 0 - 1 Q 1 0 1 C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	476 lm	113 lm/W	0 9 0 - 1 Q 1 2 1 C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	485 lm	115 lm/W	0 9 0 - 1 Q 1 1 1 C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

WIDE FLOOD ROUND 67°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	464 lm	110 lm/W	0 9 0 - 1 Q 1 9 1 D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	464 lm	110 lm/W	0 9 0 - 1 Q 1 0 1 D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	483 lm	115 lm/W	0 9 0 - 1 Q 1 2 1 D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	493 lm	117 lm/W	0 9 0 - 1 Q 1 1 1 D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

MEDIUM SQUARE 32°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	416 lm	99 lm/W	0 9 0 - 1 Q 1 9 1 E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	416 lm	99 lm/W	0 9 0 - 1 Q 1 0 1 E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	434 lm	103 lm/W	0 9 0 - 1 Q 1 2 1 E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	442 lm	105 lm/W	0 9 0 - 1 Q 1 1 1 E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

FLOOD SQUARE 55°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	464 lm	110 lm/W	0 9 0 - 1 Q 1 9 1 F <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	464 lm	110 lm/W	0 9 0 - 1 Q 1 0 1 F <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	484 lm	115 lm/W	0 9 0 - 1 Q 1 2 1 F <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	493 lm	117 lm/W	0 9 0 - 1 Q 1 1 1 F <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

Order options

CONTROL		COLOUR		REFLECTOR	
non DIM	1	gold dust RAL 260-M	9	black	B
DALI-2	3	jet black RAL 9005	B	chrome	0
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		


WIDE FLOOD SQUARE 70°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.2 W	2700 K	467 lm	111 lm/W	0 9 0 - 1 Q 1 9 1 G <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	467 lm	111 lm/W	0 9 0 - 1 Q 1 0 1 G <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	487 lm	116 lm/W	0 9 0 - 1 Q 1 2 1 G <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	497 lm	118 lm/W	0 9 0 - 1 Q 1 1 1 G <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1


UNICO Q4 ceiling

SPOT ROUND 19°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1220 lm	111 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	1220 lm	111 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	1270 lm	115 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	1300 lm	118 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1


MEDIUM ROUND 34°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1320 lm	120 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	1320 lm	120 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	1380 lm	125 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	1400 lm	127 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

FLOOD ROUND 47°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1410 lm	128 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	1410 lm	128 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	1470 lm	134 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	1500 lm	136 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

WIDE FLOOD ROUND 67°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1430 lm	130 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	1430 lm	130 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	1490 lm	135 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	1520 lm	138 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1290 lm	117 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3000 K	1290 lm	117 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	3500 K	1340 lm	122 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1
	4000 K	1370 lm	125 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 2 1

Order options

CONTROL		COLOUR		REFLECTOR	
non DIM	1	gold dust RAL 260-M	9	black	B
DALI-2	3	jet black RAL 9005	B	chrome	0
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		

FLOOD SQUARE 55°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1440 lm	131 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> ■ 2 1
	3000 K	1440 lm	131 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> ■ 2 1
	3500 K	1500 lm	136 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> ■ 2 1
	4000 K	1530 lm	139 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> ■ 2 1

WIDE FLOOD SQUARE 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1440 lm	131 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	3000 K	1440 lm	131 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	3500 K	1500 lm	136 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1
	4000 K	1530 lm	139 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> ■ 2 1

WALLWASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.0 W	2700 K	1110 lm	101 lm/W	0 9 0 - 1 Q 4 9 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	3000 K	1110 lm	101 lm/W	0 9 0 - 1 Q 4 0 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	3500 K	1160 lm	105 lm/W	0 9 0 - 1 Q 4 2 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1
	4000 K	1180 lm	107 lm/W	0 9 0 - 1 Q 4 1 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 2 1

Order options

CONTROL		COLOUR		REFLECTOR	
non DIM	<input checked="" type="checkbox"/> 1	gold dust RAL 260-M	<input checked="" type="checkbox"/> 9	black	<input checked="" type="checkbox"/> B
DALI-2	<input checked="" type="checkbox"/> 3	jet black RAL 9005	<input checked="" type="checkbox"/> B	chrome	<input checked="" type="checkbox"/> 0
		white aluminium RAL 9006	<input checked="" type="checkbox"/> G		
		traffic white RAL 9016	<input checked="" type="checkbox"/> W		