


Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
hasta 176 lm/W
L90 / 100000 h
DALI-2
IP20

Types





Colours



Inserto



Distribución luminosa



ENVIVA

track

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; suitable for mounting in 3-phase power tracks; converter in the adapter; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

ES Cuerpo de perfil de aluminio con diseño angular; forma extremadamente esbelta (solo 45 x 15 mm); sin tornillos visibles; superficie sin tratar o recubierta por pulverización; apta para la instalación en carriles electrificados de 3 fases; driver en el adaptador; inserto luminoso lineal de plástico; equipado con puntos de luz LED individuales; buen control del deslumbramiento mediante plano de punto de luz retranqueado; se ha incrementado la eficiencia debido al uso de la última tecnología en el diseño de lentes; lentes aplicadas con característica de proyección wide flood; o reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; precisa característica de emisión con distribución de luz simétrica; LEDS de eficiencia que proporcionan una alta reproducción cromática; adaptador para instalación sin herramientas o desplazamiento en diferentes carriles electrificados de 3 fases



DIN EN 12464-1
UGR ≤ 16




up to 176 lm/W
(high efficiency)



ENVIVA LENS TRACK

CRI ≥90 | UGR ≤19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | X-PERT | X-PERT




LENS DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.6 W	1204 mm	3000 K	80	3240 lm	165 lm/W	0 6 7 - 2 6 3 4 5 3 ◪ W
			90	2820 lm	144 lm/W	0 6 7 - 2 6 3 4 0 3 ◪ W
		4000 K	80	3450 lm	176 lm/W	0 6 7 - 2 6 3 4 6 3 ◪ W
			90	2820 lm	144 lm/W	0 6 7 - 2 6 3 4 1 3 ◪ W
24.8 W	1504 mm	3000 K	80	4100 lm	165 lm/W	0 6 7 - 2 6 3 5 5 3 ◪ W
			90	3570 lm	144 lm/W	0 6 7 - 2 6 3 5 0 3 ◪ W
		4000 K	80	4370 lm	176 lm/W	0 6 7 - 2 6 3 5 6 3 ◪ W
			90	3570 lm	144 lm/W	0 6 7 - 2 6 3 5 1 3 ◪ W



ENVIVA LOUVER TRACK

CRI ≥90 | UGR ≤19 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT




LOUVER DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3260 lm	165 lm/W	0 6 7 - 0 6 3 4 5 3 ◪ ■ X
			90	2840 lm	144 lm/W	0 6 7 - 0 6 3 4 0 3 ◪ ■ X
		4000 K	80	3470 lm	176 lm/W	0 6 7 - 0 6 3 4 6 3 ◪ ■ X
			90	2840 lm	144 lm/W	0 6 7 - 0 6 3 4 1 3 ◪ ■ X
25.1 W	1504 mm	3000 K	80	4120 lm	164 lm/W	0 6 7 - 0 6 3 5 5 3 ◪ ■ X
			90	3590 lm	143 lm/W	0 6 7 - 0 6 3 5 0 3 ◪ ■ X
		4000 K	80	4380 lm	175 lm/W	0 6 7 - 0 6 3 5 6 3 ◪ ■ X
			90	3590 lm	143 lm/W	0 6 7 - 0 6 3 5 1 3 ◪ ■ X



ENVIVA SPOTLINE TRACK

CRI ≥90 | UGR ≤16 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT



SPOTLINE DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3180 lm	161 lm/W	0 6 7 - 1 6 3 4 5 3 ◪ ■₁ W
			90	2770 lm	141 lm/W	0 6 7 - 1 6 3 4 0 3 ◪ ■₁ W
		4000 K	80	3390 lm	172 lm/W	0 6 7 - 1 6 3 4 6 3 ◪ ■₁ W
			90	2770 lm	141 lm/W	0 6 7 - 1 6 3 4 1 3 ◪ ■₁ W
25.1 W	1504 mm	3000 K	80	4020 lm	160 lm/W	0 6 7 - 1 6 3 5 5 3 ◪ ■₁ W
			90	3500 lm	139 lm/W	0 6 7 - 1 6 3 5 0 3 ◪ ■₁ W
		4000 K	80	4280 lm	171 lm/W	0 6 7 - 1 6 3 5 6 3 ◪ ■₁ W
			90	3500 lm	139 lm/W	0 6 7 - 1 6 3 5 1 3 ◪ ■₁ W

Order options

COLOUR ◪	
aluminium raw	0
traffic white RAL 9016	7
jet black RAL 9005	8

INSET ■	
chrome reflector	4
black reflector	8

INSET ■₁	
traffic white RAL 9016	7
jet black RAL 9005	8