



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16, UGR ≤ 19
hasta 144 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non atenuable
front IP40, back IP20

Types



Colours



Set de montaje



Distribución luminosa



SASSO 100 round high efficient adjustable

recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; light insets rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; superficie lacada; con marco; con dos luces; elementos de luz girable e inclinable; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática


360° rotatable, 30° tiltable



glare control (UGR ≤ 16)


Colour Warm Dimming 1800 – 3000 K


CRI ≥ 95 2 SDCM (optional)



SASSO 100 ROUND HIGH EFFICIENT ADJUSTABLE





SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2060 lm	133 lm/W	048 - 272391 ◪ S
	3000 K	2x2140 lm	138 lm/W	048 - 272301 ◪ S
	3500 K	2x2170 lm	140 lm/W	048 - 272321 ◪ S
	4000 K	2x2170 lm	140 lm/W	048 - 272311 ◪ S
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2730 lm	118 lm/W	048 - 272391 ◪ S
	3000 K	2x2850 lm	123 lm/W	048 - 272301 ◪ S
	3500 K	2x2880 lm	124 lm/W	048 - 272321 ◪ S
	4000 K	2x2890 lm	125 lm/W	048 - 272311 ◪ S

The data values for the luminous flux of fraction may differ for specific order options by -7%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

MEDIUM 31°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2060 lm	133 lm/W	048 - 272391 ◪ M
	3000 K	2x2150 lm	139 lm/W	048 - 272301 ◪ M
	3500 K	2x2170 lm	140 lm/W	048 - 272321 ◪ M
	4000 K	2x2180 lm	141 lm/W	048 - 272311 ◪ M
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2740 lm	118 lm/W	048 - 272391 ◪ M
	3000 K	2x2860 lm	123 lm/W	048 - 272301 ◪ M
	3500 K	2x2890 lm	125 lm/W	048 - 272321 ◪ M
	4000 K	2x2900 lm	125 lm/W	048 - 272311 ◪ M

The data values for the luminous flux of fraction may differ for specific order options by -6%. Luminous flux value refers to colour matt silver, traffic white. 2 insets necessary, order code only applies to 1 inset

FLOOD 39°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x1960 lm	127 lm/W	048 - 272391 ◪ F
	3000 K	2x2040 lm	132 lm/W	048 - 272301 ◪ F
	3500 K	2x2070 lm	133 lm/W	048 - 272321 ◪ F
	4000 K	2x2070 lm	134 lm/W	048 - 272311 ◪ F
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2610 lm	113 lm/W	048 - 272391 ◪ F
	3000 K	2x2720 lm	117 lm/W	048 - 272301 ◪ F
	3500 K	2x2750 lm	119 lm/W	048 - 272321 ◪ F
	4000 K	2x2760 lm	119 lm/W	048 - 272311 ◪ F

The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

Order options


COLOUR ◪	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

WIDE FLOOD 56°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2120 lm	136 lm/W	048-272391 W
	3000 K	2x2200 lm	142 lm/W	048-272301 W
	3500 K	2x2230 lm	144 lm/W	048-272321 W
	4000 K	2x2240 lm	144 lm/W	048-272311 W
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2820 lm	121 lm/W	048-272391 W
	3000 K	2x2930 lm	127 lm/W	048-272301 W
	3500 K	2x2970 lm	128 lm/W	048-272321 W
	4000 K	2x2980 lm	128 lm/W	048-272311 W

2 insets necessary, order code only applies to 1 inset

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 0
DALI cable ø 4 – 12 mm	105·58·30	005-255111 0

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L·W·H (mm)	ORDER CODE
218·118·35	048-279831 [1]


Electrical accessories (required)

POWER SUPPLY PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA | 21 W | non DIM	198-264 V AC	η 86 %	143·43·30	002-90766
450 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90767
650 mA | 28 W | non DIM	198-264 V AC	η 88 %	143·43·30	002-90780
650 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90789

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR [1]	
traffic white RAL 9016	7
jet black RAL 9005	8
white aluminium RAL 9006	G

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40 V SELV

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA | DALI-2	176-264 V AC	η 85 %	002-90767A
650 mA | DALI-2	176-264 V AC	η 85 %	002-90789A
700 mA | DALI-2	176-264 V AC	η 85 %	002-90776A
450 mA | non DIM	198-264 V AC	η 88 %	002-90766A
650 mA | non DIM	198-264 V AC	η 88 %	002-90780A
700 mA | non DIM	198-264 V AC	η 88 %	002-90774A

2 power supplies for 2 lamps variants necessary

Optical accessories (optional)



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø·H (mm)	ORDER CODE
jet black	50·3	007-1965598