Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 19
hasta 144 lm/W
L80 / 50000 h
DALI-2, non atenuable
front IP44, back IP20

Types

Colours

Set de montaje

Distribución luminosa

SASSO 60 round high efficient down-light

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática

glare control (UGR ≤ 16)

60 mm recessed depth (non DIM)

quick mounting in soft acoustic ceilings

Colour Warm Dimming 1800 – 3000 K

SASSO 60 round high efficient downlight

360° | CRI ≥ 90 | 2 SDCM | UGR ≤ 19 | cd/m² ≤ 1500 | III | 1 ADDR. | IP20 IP44 | X-PERT

MEDIUM 28°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.0 W, 36 Vf, 300 mA	2700 K	1360 lm	136 lm/W	048-260391 M
	3000 K	1420 lm	142 lm/W	048-260301 M
	4000 K	1440 lm	144 lm/W	048-260311 M
11.1 W, 36 Vf, 300 mA	3500 K	1430 lm	129 lm/W	048-260321 M

The data values for the luminous flux of fraction may differ for specific order options by -11%. Luminous flux value refers to colour traffic white.

FLOOD 31°-32°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.0 W, 36 Vf, 300 mA	2700 K	1350 lm	135 lm/W	048-260391 F
	3000 K	1400 lm	140 lm/W	048-260301 F
	4000 K	1420 lm	142 lm/W	048-260311 F
11.1 W, 36 Vf, 300 mA	3500 K	1420 lm	128 lm/W	048-260321 F

The data values for the luminous flux of fraction may differ for specific order options by -12%. Luminous flux value refers to colour traffic white.

WIDE FLOOD 41°-42°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.0 W, 36 Vf, 300 mA	2700 K	1280 lm	128 lm/W	048-260391 W
	3000 K	1330 lm	133 lm/W	048-260301 W
	4000 K	1350 lm	135 lm/W	048-260311 W
11.1 W, 36 Vf, 300 mA	3500 K	1350 lm	121 lm/W	048-260321 W

The data values for the luminous flux of fraction may differ for specific order options by -17%. Luminous flux value refers to colour traffic white.

SUPER WIDE FLOOD 61°-62°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.0 W, 36 Vf, 300 mA	2700 K	1330 lm	133 lm/W	048-260391 X
	3000 K	1390 lm	139 lm/W	048-260301 X
	4000 K	1410 lm	141 lm/W	048-260311 X
11.1 W, 36 Vf, 300 mA	3500 K	1400 lm	126 lm/W	048-260321 X

The data values for the luminous flux of fraction may differ for specific order options by -12%. Luminous flux value refers to colour traffic white.

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 0
DALI cable ø 4 – 12 mm	105·58·30	005-255111 0

Linect®-Ready

Mounting accessories (required)

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9



MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/20/25 mm	73·29	048-2696117

for SASSO 60 round | SPIO 60 downlight



MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	80·25	048-2696197



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·27	048-2696397
jet black	80·27	048-2696398



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·40	048-2696317
jet black	80·40	048-2696318
white aluminium	80·40	048-2696316

Mounting accessories (optional)

EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	048-2695210



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-2695110

order mounting set separately

Mounting tools accessories (optional)

MOUNTING TOOL for soft acoustic ceilings

COLOUR	L·W·H (mm)	ORDER CODE
traffic black	77·77·35	048-2695918

Electrical accessories (required)

POWER SUPPLY 300 mA, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
non DIM	η 84 %	85·40·22	002-90771
DALI-2	η 87 %	165·29·21	002-90790

2 power supplies for 2 lamps variants necessary

Order options

COLOUR

white aluminium	RAL 9006
traffic black	RAL 9017

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-6520210

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-6121030

200 -1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	002-90790A
250 mA | 15 W | DALI-2	η 87 %	002-90748A
300 mA | 15 W | non DIM	η 84 %	002-90771A
250 mA | 10 W | non DIM	η 80 %	002-90742A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	002-90770
250 mA	η 87 %	185·30·21	002-90747

2 power supplies for 2 lamps variants necessary