



SASSO 60 round

suspended


EN Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy

FR Spot cylindrique en aluminium ; surface de l'insert d'éclairage peinte ; surface du boîtier thermolaquée ; suspension par câble ; câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM
UGR ≤ 13 , UGR ≤ 16 , UGR ≤ 19
jusqu'à 94 lm/W
L80 / 50000 h
DALI-2, non DIM
IP20

Types



Couleur



Couleur intérieure



Répartition de la lumière




glare control
(UGR ≤ 16)



easy mounting
no visible
screws



CRI ≥ 95 2
SDCM
(optional)



SASSO 60 round downlight suspended



SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.4 W	2700 K	754 lm	73 lm/W	0 4 8 - 3 1 H 0 9 S
	3000 K	778 lm	75 lm/W	0 4 8 - 3 1 H 0 0 S
	3500 K	795 lm	76 lm/W	0 4 8 - 3 1 H 0 2 S
	4000 K	819 lm	79 lm/W	0 4 8 - 3 1 H 0 1 S

The data values for the luminous flux may differ for specific order options by -7%. Luminous flux value refers to inner colour traffic white.

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.2 W	2700 K	888 lm	87 lm/W	0 4 8 - 3 1 H 0 9 M
	3000 K	921 lm	90 lm/W	0 4 8 - 3 1 H 0 0 M
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 M
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 M

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.2 W	2700 K	845 lm	83 lm/W	0 4 8 - 3 1 H 0 9 F
	3000 K	877 lm	86 lm/W	0 4 8 - 3 1 H 0 0 F
	3500 K	896 lm	88 lm/W	0 4 8 - 3 1 H 0 2 F
	4000 K	915 lm	90 lm/W	0 4 8 - 3 1 H 0 1 F

The data values for the luminous flux may differ for specific order options by -14%. Luminous flux value refers to inner colour traffic white.

WIDE FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.2 W	2700 K	887 lm	87 lm/W	0 4 8 - 3 1 H 0 9 W
	3000 K	920 lm	90 lm/W	0 4 8 - 3 1 H 0 0 W
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 W
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

HEIGHT	H	CONTROL		COLOUR		INNER COLOUR	
75 mm	2	non DIM	1	jet black RAL 9005	1	jet black	1
150 mm	7	DALI-2	3	traffic white RAL 9016	7	matt silver	4
						traffic white	7
						gold dust	9

James Good Coiffeur LoungeaJames Good For You GmbH, Flums

Suisse

Architecte

Daniel Huber Architektur
GmbH

Lighting Design

Daniel Huber Architektur
GmbH

Photographe

Bruno Helbling



Produits utilisés



**SASSO 60 round
suspended**



TULA suspended



**SASSO 60 round
recessed 1 lamp**



