

HEX-O

ceiling

EN Hexagonal luminaires & acoustic elements, suitable for single or group installation; quick mounting system without tools; light housing from extruded aluminium profile, seamlessly welded; surface powder coated; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; plug-in terminals for through wiring; acoustic elements: MODULE in the luminaires' dimensions, FLAT with reduced height, ABSORBER to combine with other housings; acoustic element made of high-quality, recycled PET felt; improvement of room acoustics through absorption and scattering of sound waves


FR Luminaires & éléments acoustiques hexagonaux, adaptés pour montage individuel et groupé ; système de montage rapide, sans outil ; corps de luminaire en profilé extrudé en aluminium, soudé sans trace visible ; surface thermolaquée ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; borne enfichable pour câblage traversant ; éléments acoustiques : MODULE dans les dimensions des luminaires, FLAT à hauteur réduite, ABSORBER pour combinaison avec d'autres corps et éléments ; éléments acoustiques en feutre PET recyclé, haute qualité ; amélioration de l'acoustique grâce à l'absorption et à la dispersion du son

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 3000 cd/m²
 up to 142 lm/W
 L90 @ 50 000 h
 DALI-2
 opal, microprismatic (UGR ≤ 19)

acoustic elements
 up to absorption class A
 🔥 available as B-s1, d0

Types



Luminaire colours



Acoustic colours




Light distribution




direct



DiiA® standards
 251, 252, 253



DIN EN 12464-1
 UGR ≤ 19



tunable white
 2700–6500 K

Order options

COLOUR TEMPERATURE

3000K	5
4000K	6

CONTROL

DALI-2

LUMINAIRE COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8
special colours p. 992	X

ACOUSTIC COLOUR

○ white	W
● marble grey	D
● felt grey	G
● black	L
special colours p. 992	X

LIGHT OPTIC COVER

opal	O
microprismatic (UGR ≤ 19)	P

Options on request


COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K

DALI-2 DT8



HEX-O 500 ceiling



UGR ≤ 19

cd/m² ≤ 3000

RG0 IEC 62471

DALI 1 ADDR.


220-240V

X-PERT

X-PERT

SINGLE AND GROUP MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
16.3W	3000K	2160lm	073-61511 3 3 3
	4000K	2290lm	



HEX-O 750 ceiling



UGR ≤ 19

cd/m² ≤ 3000

RG0 IEC 62471

DALI 2 ADDR.


220-240V

X-PERT

X-PERT

SINGLE AND GROUP MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
35W	3000K	4680lm	073-61611 3 3 3
	4000K	4960lm	



HEX-O 1000 ceiling



UGR ≤ 19

cd/m² ≤ 3000

RG0 IEC 62471

DALI 2 ADDR.

220-240V

X-PERT

X-PERT

SINGLE AND GROUP MOUNTING


SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
68W	3000K	9110lm	073-61711 3 3 3
	4000K	9640lm	

Acoustic elements

HEX-O MODULE ceiling

SINGLE AND GROUP MOUNTING


TYPE	ORDER CODE
MODULE 500 ceiling	073-691510
MODULE 750 ceiling	073-691610
MODULE 1000 ceiling	073-691710



HEX-O MODULE FLAT ceiling

SINGLE AND GROUP MOUNTING

TYPE	ORDER CODE
MODULE FLAT 750 ceiling	073-691620
MODULE FLAT 1000 ceiling	073-691720




HEX-O ABSORBER

SINGLE AND GROUP MOUNTING

TYPE	ORDER CODE
ABSORBER 750*	073-691640
ABSORBER 1000**	073-691740

*only in combination with HEX-O 500 or MODULE 500

**only in combination with HEX-O 750, MODULE 750 or FLAT 750





HEX-O

suspended (single mounted)

EN Hexagonal luminaires & acoustic elements; suitable for single installation; pendant fitting with cable suspension (3 cables); height adjustment without tools; light housing from extruded aluminium profile, seamlessly welded; powder coated; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; transparent feed, canopy for through wiring (included); acoustic element made of high-quality, recycled PET felt: MODULE in the luminaires' dimensions, FLAT with reduced height, ABSORBER to combine with other housings; improvement of room acoustics (absorption & scattering of sound waves)


FR Luminaires & éléments acoustiques hexagonaux ; adaptés pour un montage unique ; suspension par câble (3 câbles) ; réglage en hauteur sans outil ; corps de luminaire en profilé extrudé en aluminium, soudé sans trace visible ; thermolaquée ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; ligne d'alimentation transparente, cache-piton pour câblage continu (inclus) ; éléments acoustiques en feutre PET recyclé, haute qualité : MODULE aux dimensions des luminaires, FLAT de hauteur réduite, ABSORBER pour combinaison avec d'autres corps ; amélioration de l'acoustique (absorption & dispersion du son)

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
UGR ≤ 19 / 65° ≤ 3000 cd/m²
up to 142 lm/W
L90 @ 50 000 h
DALI-2
opal, microprismatic (UGR ≤ 19)

acoustic elements
up to absorption class A
🔥 available as B-s1, d0


Types



Luminaire colours




Acoustic colours




Light distribution



DiiA® standards
251, 252, 253



DIN EN 12464-1
UGR ≤ 19



tunable white
2700-6500 K

Order options

COLOUR TEMPERATURE

3000K	5
4000K	6

CONTROL

DALI-2

LUMINAIRE COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8
● special colours* p.992	X

*canopy in white or black

ACOUSTIC COLOUR

○ white	W
● marble grey	D
● felt grey	G
● black	L
● special colours p.992	X

LIGHT OPTIC COVER

opal	O
microprismatic (UGR ≤ 19)	P

Options on request


COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K

DALI-2 DT8




HEX-O 500 suspended



SINGLE MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
16.3W	3000K	2160lm	073-62511 3 3 3
	4000K	2290lm	




HEX-O 750 suspended



SINGLE MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
35W	3000K	4680lm	073-62611 3 3 3
	4000K	4960lm	



HEX-O 1000 suspended



SINGLE MOUNTING



SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
68W	3000K	9110lm	073-62711 3 3 3
	4000K	9640lm	

Acoustic elements

HEX-O MODULE suspended

SINGLE MOUNTING


TYPE	ORDER CODE
MODULE 500 suspended	073-692510
MODULE 750 suspended	073-692610
MODULE 1000 suspended	073-692710



HEX-O MODULE FLAT suspended

SINGLE MOUNTING

TYPE	ORDER CODE
MODULE FLAT 750 suspended	073-692620
MODULE FLAT 1000 suspended	073-692720




HEX-O ABSORBER

SINGLE MOUNTING

TYPE	ORDER CODE
ABSORBER 750*	073-691640
ABSORBER 1000**	073-691740

*only in combination with HEX-O 500 or MODULE 500

**only in combination with HEX-O 750, MODULE 750 or FLAT 750



HEX-O

suspended (group mounted)

EN Hexagonal luminaires & acoustic elements; suitable for group installation; pendant fitting with cable suspension (1 cable); height adjustment without tools; rear rail for alignment; light housing from extruded aluminium profile, seamlessly welded; powder coated; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; transparent feed, canopy for through wiring (separately available); acoustic element made of high-quality, recycled PET felt: MODULE in the luminaires' dimensions, FLAT with reduced height, ABSORBER to combine with other housings; improvement of room acoustics (absorption & scattering of sound waves)

FR Luminaires & éléments acoustiques hexagonaux ; adaptés pour installation groupée ; suspension par câble (1 câble) ; réglage en hauteur sans outil ; rail arrière pour l'alignement ; corps de luminaire en profilé extrudé en aluminium, soudé sans trace visible ; thermo-laquée ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; ligne d'alimentation transparente, cache-piton pour câblage continu (à commander séparément) ; éléments acoustiques en feutre PET recyclé, haute qualité : MODULE aux dimensions des luminaires, FLAT de hauteur réduite, ABSORBER pour combinaison avec d'autres corps ; amélioration de l'acoustique (absorption & dispersion du son)


Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
UGR ≤ 19 / 65° ≤ 3000 cd/m²
up to 142 lm/W
L90 @ 50 000 h
DALI-2
opal, microprismatic (UGR ≤ 19)


acoustic elements
up to absorption class A
🔥 available as B-s1, d0

Types


luminaires




acoustic module




acoustic module flat



Luminaire colours



Acoustic colours




Light distribution




direct



DiiA® standards
251, 252, 253



DIN EN 12464-1
UGR ≤ 19



tunable white
2700–6500 K

Order options

COLOUR TEMPERATURE

3000K	5
4000K	6

CONTROL

DALI-2

LUMINAIRE COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8
special colours* p. 992	X

*canopy in white or black;
not for power feeder

ACOUSTIC COLOUR

○ white	W
● marble grey	D
● felt grey	G
● black	L
special colours p. 992	X

LIGHT OPTIC COVER

opal	O
microprismatic (UGR ≤ 19)	P

Options on request







COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K

DALI-2 DT8



LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal

HEX-O 500 suspended



GROUP MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
16.3W	3000K	2160lm	0 7 3 - 6 3 5 1 3 3 3
	4000K	2290lm	

HEX-O 750 suspended



GROUP MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
35W	3000K	4680lm	0 7 3 - 6 3 6 1 3 3 3
	4000K	4960lm	

HEX-O 1000 suspended



GROUP MOUNTING

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
68W	3000K	9110lm	0 7 3 - 6 3 7 1 3 3 3
	4000K	9640lm	

Electrical accessories

CANOPY

TYPE	L (mm)	ORDER CODE
canopy / feeder cable 5 × 1.5 mm²	1500	0 0 5 - 2 2 3 2 4 1 3

one per group needed; can be placed above luminaires or acoustic elements
for electrical system configuration see luminaire data sheet at xal.com

Acoustic elements

HEX-O MODULE suspended

GROUP MOUNTING

TYPE	ORDER CODE
MODULE 500 suspended	0 7 3 - 6 9 3 5 1 0 3
MODULE 750 suspended	0 7 3 - 6 9 3 6 1 0 3
MODULE 1000 suspended	0 7 3 - 6 9 3 7 1 0 3

HEX-O MODULE FLAT suspended

GROUP MOUNTING

TYPE	ORDER CODE
MODULE FLAT 750 suspended	0 7 3 - 6 9 3 6 2 0 3
MODULE FLAT 1000 suspended	0 7 3 - 6 9 3 7 2 0 3

HEX-O ABSORBER

GROUP MOUNTING

TYPE	ORDER CODE
ABSORBER 750*	0 7 3 - 6 9 1 6 4 0 3
ABSORBER 1000**	0 7 3 - 6 9 1 7 4 0 3

*only in combination with HEX-O 500 or MODULE 500

**only in combination with HEX-O 750, MODULE 750 or FLAT 750